ComX Computers
Product Specification Sheet

NET-TL-SM321A

TP-Link TL-SM321A 1000Base-BX WDM Bi-Directional SFP Module

Product Overview

TP-Link TL-SM321A 1000Base-BX WDM Bi-Directional SFP Module, LC connector, TX:1550nm/RX:1310nm, single-mode, 10km



Specifications

Overview:

TP-LINK´s TL-SM321A adopts the latest standard 1000Base-BX, transmission over a single strand of fiber, with one different wavelength going in each direction. You can extend the network distance up to 10Km with TP-LINK´s Routers, Switches, Media Converters to provide high speed and stability.

Features:

- Supports WDM Bi-Directional technology, using a single strand of fiber
- TX: 1550nm / RX: 1310nm
- Internal +3.3V Power Supply
- In pairs with TL-SM321B
- Plug-and-Play
- Suitable Products: TL-SG5428, TL-SL5428E, TL-SG3210/3216/3424/3424P, TL-SL3428/3452, TL-SG2216/2424, TL-SL2210WEB/2218WEB/2428WEB/2452WEB, TL-SL1351 and MC200L

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	NET-TL-SM321A
MEDIA CONVERTER & MODULE	
Standards and Protocols	IEEE 802.3z, CSMA/CD, TCP/IP

Wave Length	TX: 1550nm / RX: 1310nm
Power Supply	3.3V
Safety & Emission	FCC, CE
Cabel	Single-mode Fiber
Fiber Type	9/125 um Single-mode
Max. Cable Length	10km
Data Rate	1.25Gbps
Port Type	LC/UPC
Environment	Operating Temperature: 0 ~70 (32 ~158)
	Storage Temperature: -40 ~80 (-40 ~176)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/NET-TL-SM321A-TP-Link-TL-SM321A-1000Base-BX-WDM-Bi-Directional-SFP-Module-p-197576.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 10:17:23.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.