ComX Computers
Product Specification Sheet

PRCALBP6030

Canon i-SENSYS LBP6030 A4 Mono Laser Printer

Product Overview

Canon i-SENSYS LBP6030 A4 Mono Laser Printer, 18ppm, 150 Sheet paper tray, 2400 x 600dpi with AIR, FPOT 7.8sec, 2W in Sleep mode, Server 2003/8, XP, Vista/Win7/Win8/Win8.1, Mac & Linux web distribution Only, CRG 725 Starter, Wi-Fi, CA725BK



Specifications

Overview:

An affordable, space saving mono laser printer designed for personal or small office use. Quiet, reliable and highly energy efficient with low power consumption it delivers fast, high quality prints.

Features:

Space saving, mono laser printer
Designed to fit comfortably on the desk, this fast, compact and affordable mono laser printer is perfect for personal and small office use. Its sleek, space-saving design includes a retractable paper tray cover and keeps dimensions to a mere 364 x 249 x 198 mm (W x D x H).

Fast, productive performance
The i-SENSYS LBP6030 springs into the action the moment you need it thanks to Canon's Quick First-Print technologies, which ensure quick recovery from sleep mode. With a First Print Out Time (FPOT) of just 7.8 seconds and professional laser print speeds of 18 ppm there's no waiting around for your prints - so you can quickly get back to what's important.

Exceptional laser quality
Enjoy the sharpest, crispest text and most detailed graphics thanks to a print resolution of up to 2400 x 600 dpi with Automatic Image Refinement. Our MS (Magnetic Spherical) Toner has been specifically developed to deliver optimum results print after print.

Energy efficient
Thanks to Canon's On Demand fixing technology this energy efficient printer uses only 0.8 watts in sleep mode and there's virtually no warm up time. A convenient front power switch makes it easy to turn off, cutting energy costs and reducing its environmental impact even further.

Quiet operation

Thanks to Canon's engine design, the i-SENSYS LBP6030 is silent in standby mode and exceptionally quiet during operation - so you can focus on your work without distraction.

All-in-One cartridge

The recyclable All-in-One cartridge ensures maintenance-free operation and reliable high quality output. The Authentic Canon Laser Cartridge contains toner, drum and cleaning units and can be replaced in seconds without any fuss or mess.

Specifications:

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	PRCALBP6030
PRINTER ENGINE	
Print speed	18ppm mono (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	600 x 600 dpi
Warm-up time	Approx. 1 second from Sleep
	10 seconds or less from power on
First Page Out Time	Approx. 7.8 seconds or less
Duty cycle	Max 5,000 pages per month
Print margins	5 mm-top, bottom, left and right
MEDIA HANDLING	
Paper input (Standard)	150-sheet multi-purpose tray
Paper output	100-sheet face down
Media types	Plain paper, Heavy Paper, Transparency
	Label, Envelope
Media sizes	A4/B5/A5/LGL/LTR/EXE/16K/Custom size
	Env. COM10/Env. Monarch/Env. C5/Env. DL
	width76.2~216mm x length 188~356mm
Media weights	Multi-purpose tray:
	60 to 163 g/m
GENERAL FEATURES	
Power requirements	AC 220-240V (+/-10%), 50/60Hz (+/-2Hz)

Power consumption	Maximum: Approx. 870 W or less
	Active: Average approx. 330 W
	Standby: Average approx. 1.8 W or less
	Sleep: Average approx. 0.8 W or less
	Typical Electricity Consumption (TEC): 0.47 kWh/week
	Lot26
Noise level	Sound power:
	Active: 6.34 B or less
	Standby: Inaudible
	Sound pressure:
	Active: 49.2 dB(A)
	Standby: Inaudible
Dimensions (W x D x H)	364 mm x 249 mm x 199 mm
Weight	Approx. 5.0 kg
Operating environment	Temperature: 10~30ºC
	Humidity: 20~80%RH (no condensation)
Control panel	2 LED indicators, 2 operation KEY
CONTROLLER	
Memory	32 MB
Printer languages	UFRII LT
Interface and connectivity	USB 2.0 Hi-Speed
Operating systems compatibility	Win 8.1(32/64bit)/Win 8(32/64bit)/Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit)/Server 2012(32/64bit)/Server 2012 R2(64bit)/
	Server 2008(32/64bit) / Server 2008 R2(64bit)/ 2003 Server(32/64bit)/
	Mac OS X 10.6~ /Linux /Citrix(FR2)
CONSUMABLES	
All-in-One cartridges	Standard: Cartridge 725 (1, 600 pages)
Print speed	The print speed may drop depending on the printer driver settings, paper size, paper type and number of pages printed
Noise level	Declared noise emission in accordance with ISO 9296
Operating systems compatibility	Web distribution only
All-in-One cartridges	Based on ISO/IEC 19752
	Printer ships with 700 pages starter cartridge

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/PRCALBP6030-Canon-i-SENSYS-LBP6030-A4-Mono-Laser-Printer-p-108699.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-08 08:39:58.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.