ComX Computers
Product Specification Sheet

PRLE26Z0148

Lexmark MX910DE Mono A3 4-in-1 Printer, Color Scanning, Copying Faxing, Network Scanning, Printing

Product Overview

Lexmark MX910DE Mono A3 4-in-1 Printer, 45cpm, x, 2400 I Q, 1024MB, USB, GB Ethernet, USB direct interface, Duplex,2 x 500 Sheet Drawer., 64G0H00 , 54G0P00 , 54G0W00



Specifications

Overview:

Advanced features and output-size options

High-volume output, long-life components, solid security and advanced finishing make the Lexmark MX910de the foundation of SRA3 / 12"x18"-capable multifunction monochrome products from Lexmark.

Features:

A3 / Tabloid output

Show the big picture that typical printers can't produce, with up to SRA3 / 12"x18" printing capability.

Enterprise volume

Meet your most demanding output requirements with 45 pages per minute, input capacity up to 6,650 pages and a 200,000-page maximum monthly duty cycle.

Sustainability

Reduce your environmental footprint with long-life replaceable components, fast wake-up, energy-saving modes and duplex printing.

Connectivity

Connect nearly everyone with Gigabit Ethernet, USB and optional parallel ports plus optional wireless and mobile printing.

Advanced finishing

Stapling, offset stacking, hole-punching and both trifold and saddle-stitched booklets give users finishing options for many different needs.

Lexmark e-Task interface

Access on-screen solutions to customize the user experience, integrate with other devices and meet business process needs.

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	PRLE26Z0148
Part Number	26Z0100
Print Technology	Monochrome Laser
Function	Color Scanning
	Copying
	Faxing
	Network Scanning
	Printing
Workgroup Size	Departmental Workgroup
Touch Screen Display	Yes
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen
Print Speed (Letter, Black)	Up to 45 ppm
Print Speed (Letter, Black) Duplex	Up to 45 spm
Time to First Page (Black)	As fast as < 5.6 seconds
Duplex (2-sided) Printing	Integrated Duplex
Print Resolution, Black	1200 Image Quality
	1200 x 1200 dpi
	2400 Image Quality
	600 x 600 dpi
Copy Speed (Letter, Black)	Up to 45 cpm
Copy Speed (Letter, Black) Duplex	Up to 45 spm

Time to First Copy (Black)	As fast as 5.8 seconds
Reduce / Enlarge Range	25 - 400 %
Simplex Scan Speed (A4/Ltr, Black)	Up to 80 sides per minute
Simplex Scan Speed (A4/Ltr, Color)	Up to 80 sides per minute
Duplex Scan Speed (A4/Ltr, Black)	Up to 140 sides per minute
Duplex Scan Speed (A4/Ltr, Color)	Up to 140 sides per minute
Scan Area, Maximum	11.69 x 17.0 inches
ADF Scan	DADF (Single Pass Duplex)
Scanner Type	Flatbed scanner with ADF
Scan Technology	CIS / CCD Hybrid
Optical Scanning Resolution	600 X 600 ppi (black)
	600 X 600 ppi (color)
Scan File Formats (Send as)	JPEG, JPG
	PDF
	Secure PDF
	TIFF
	XPS
	Archival PDF (A-1a, A-1b)
	Searchable PDF (optional OCR with 1GB RAM and hard disk required)
	Highly compressed PDF (1GB RAM and hard disk required)
Scan Destinations	e-mail
	FTP
	USB Flash drive
	USB or Network connected computer
	Lexmark Document Solutions Suite (LDSS)
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Fax Transmission Speed	< 3 seconds per page
Processor	Dual Core, 800 MHz
Memory, Standard	1024 MB
Memory, Maximum	3072 MB
Hard Disk	Included in configuration
Apple Operating Systems Supported	Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10)

Linux Operating Systems Supported	SUSE Linux Enterprise Server 10, 11
	SUSE Linux Enterprise Desktop 10, 11
	Red Flag Linux Desktop 6.0
	Linpus Linux Desktop 9.6
	Debian GNU/Linux 5.0, 6.0
	Red Hat Enterprise Linux WS 4.0, 5.0, 6.0
	PCLinuxOS 2011
	Mint 10, 11, 12, 13
	openSUSE 11.4, 12.1, 12.2
	Ubuntu 12.04, 12.10
	Fedora 17, 18, 19
Microsoft Windows Operating Systems Supported	Windows XP
	Windows Server 2003
	Windows XP x64
	Windows Server 2003 x64
	Windows Vista
	Windows Vista x64
	Windows Server 2008
	Windows Server 2008 x64
	Windows 7
	Windows 7 x64
	Windows Server 2008 R2
	Windows 8
	Windows 8 x64
	Windows Server 2012
	Windows 8.1
	Windows 8.1 x64
	Windows Server 2012 R2
	Windows RT
	Windows RT 8.1
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server
	Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS)
	Novell Open Enterprise Server on SUSE Linux Enterprise Server
UNIX Operating Systems Supported	HP-UX 11.11, 11.23, 11.31
	Sun Solaris SPARC 9, 10, 11
	Sun Solaris x86 10, 11
	IBM AIX 5.3, 6.1, 7.1

Included Paper Handling	250-Sheet Output Bin
	150-Sheet Multipurpose Feeder
	2 x 500-Sheet Input
Optional Paper Handling	Staple Punch Finisher
	Inline Stapler
	2500-Sheet Tandem Tray
	3000-Sheet Tray
	Booklet Finisher
	2 x 500-Sheet Tray
Paper Input Capacity, Standard	Up to 1150 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum	Up to 6650 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard	Up to 250 pages 20 lb or 75 gsm bond
Paper Output Capacity, Maximum	Up to 3500 pages 20 lb or 75 gsm bond
Paper Weight Range Supported - Standard Tray (lb.)	16 - 68 lb.
Paper Weight Range Supported - Multipurpose Feeder (lb.)	16 - 68 lb.
A3 / 11 x 17	Yes
ADF	100-Sheet Automatic Document Feeder
ADF Paper Input Capacity	Up to 100 pages 20 lb or 75 gsm bond
ADF Paper Output Capacity	Up to 100 pages 20 lb or 75 gsm bond
Finishing Option	Yes
Finishing Functions	Offset stacking
	Stapling
	Hole punching
	Booklet fold and saddle stapling
Number of Paper Inputs, Standard	3
Number of Paper Inputs, Maximum	6
Media Types Supported	Card Stock
	Envelopes
	Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide.

Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	9 Envelope
	A3
	A4
	A5
	B5 Envelope
	C5 Envelope
	DL Envelope
	Executive
	Folio
	JIS-B4
	JIS-B5
	Ledger
	Legal
	Letter
	Statement
	Universal
	Super tabloid (12 x 18 in.)
	Oficio
	A6
	SRA3
Standard Ports	One Internal Card Slot
	USB 2.0 Specification Hi-Speed Certified (Type B)
	Gigabit Ethernet (10/100/1000)
	Front USB 2.0 Specification Hi-Speed Certified Port (Type A)
	Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)
Optional Local Ports	Internal RS-232C serial
	Internal 1284-B Bidirectional Parallel
Optional Network Ports	Internal MarkNet N8350 802.11b/g/n Wireless
Direct USB	Yes
Ethernet Network	Yes
Network Protocol Support	TCP/IP IPv4
	AppleTalk
	TCP/IP IPv6
	TCP
	UDP

Network Printing Methods	LPR/LPD
	Direct IP (Port 9100)
	Enhanced IP (Port 9400)
	Secure IP (Port 96xx)
	FTP, TFTP
	ThinPrint .print integration
	Telnet
	IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)
	Microsoft Web Services WSD
	Pull Printing
Network Management Protocols1	HTTP
	HTTPs (SSL/TLS)
	SNMPv1, SNMPv2c
	SNMPv3
	WINS
	IGMP
	BOOTP, RARP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
	IPSec
Printable Area	0.167, .12, .12, .12 inches of the top, bottom, right and left edges (within)

Printer Languages (Standard)	PCL 5e Emulation
	PCL 6 Emulation
	Personal Printer Data Stream (PPDS)
	PostScript 3 Emulation
	xHTML
	Direct Image
	Microsoft XPS (XML Paper Specification)
	AirPrint
	PDF 1.7 emulation
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	158 scalable PostScript fonts
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Laser Cartridge Yields5	32, 500-page High Yield Cartridge
Photoconductor Estimated Yield	Up to 125000 pages, based on 3 average letter/A4-size pages per print job
Cartridge(s) Shipping with Product	21, 000-page Starter Toner Cartridge
Packaged Size (in. - H x W x D)	47 x 30 x 33 in.
Packaged Weight (lb.)	246 lb.
Size (in. - H x W x D)	35.8 x 24.2 x 27.4 in.
Weight (lb.)	209.4 lb.
Size, Trays Extended (in. - H x W x D)	51.44 x 37.5 x 49.07 in.
Noise Level, Idle	29 dBA
Noise Level (Print), Operating	52 dBA
Duplex Print Noise Level, Operating	55 dBA
Noise Level (Copy), Operating	53 dBA
Noise Level (Scan), Operating	57 dBA
ENERGY STAR	Yes
Average Power (Hibernate Mode)	0.6 watts
Average Power (Sleep Mode)	3.6 watts
Average Power (Ready Mode)	220 watts
Average Power (Printing)	865 watts
Average Power (Copying)	880 watts

Average Power (Scanning)	230 watts
ENERGY STAR Typical Electricity Consumption (TEC)	3.7 kilowatt-hours per week
Product Certifications	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, cTUV, US FDA/CDRH, cTUVus, IEC 60825-1, CB Report, NCC Mark, FCC, CE (EU) DoC, EFTA (CE), KCC, RCM, CCC, C-tick DoC, EuP, CECP, CEL, ECMA-370, TED, GOST-R, SII, TER, Bel GISS, SABS, TUV-AR, KC mark, BIS, TUV-GS Mark
Maximum Monthly Duty Cycle	Up to 200000 pages per month
Recommended Monthly Page Volume	15000 - 50000 pages
Specified Operating Environment	Altitude: 0 - 2500 Meters (8, 200 Feet)
	Humidity: 15 to 85% Relative Humidity
	Temperature: 10 to 30 degreesC (50 to 86 degreesF)
Country of Origin	China (PR)
UNSPSC Code	43212110
Harmonized Tariff Code	8443.31.0000

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/PRLE26Z0148-Lexmark-MX910DE-Mono-A3-4-in-1-Printer-Color-Scanning-Copying-Faxing-p-122018.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-19 13:10:30.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.