

PRLE34S0816

Lexmark E462dtn Network and Duplex Ready Mono Laser Printer

Product Overview

Lexmark E462dtn Network and Duplex Ready Mono Laser Printer with 550 Sheet Drawer, 38ppm Print Speed, 1200dpi Print Resolution, 64MB Standard Memory, USB/Parallel/Ethernet Connectivity, 466 MHz Processor, 4-Line Operator Panel with Numeric Pad.



Specifications

Features:

Compact Yet Commanding

The Lexmark E462dtn is ultra-compact yet provides the largest standard input capacity and toner capacity in the E460 Series. With two 250-sheet paper inputs plus a 50-sheet multipurpose feeder, you'll have plenty of paper for your busiest workdays.

Lexmark E462dtn Exclusive Savings

The Lexmark E462dtn offers the highest yield replacement cartridge in the E460 Series: 18,000* pages. Choose this Lexmark Extra High Yield Toner Cartridge at replacement time and see just how low your cost per page can go. (*Declared yield in accordance with ISO/IEC 19752.)

Lexmark E462dtn Easy to Perform and Save

True 1200 x 1200 dpi print quality and performance features like a time-to-first-page as fast as 6.5 seconds help you perform at your best. Built-in networking lets you share the Lexmark E462dtn with others, and built-in duplexing makes it easy to save paper.

Lexmark E462dtn Fuss Less, Focus More

Brings hassle-free printing to your fingertips. Experience enhanced security and time savings with a range of high-end features you typically wouldn't expect to find on such an attractively priced printer, like a numeric pad for confidential printing, early-warning alerts for low toner, and customizable operator panel messaging.

Lexmark E462dtn Print Black, Think Green

Designed with eco-conscious features like Eco-Mode and an instant warm-up fuser to help you save paper and energy. Recycle your empty cartridges free of charge through the Lexmark Cartridge Collection Program. Printing responsibly means everyone wins-your business, your budget and the environment!

ComX Computers

Product Specification Sheet

Specifications:

Print Technology	Monochrome Laser
Print Resolution, Black	1200 Image Quality
	1200 x 1200 dpi
	2400 Image Quality
	600 x 600 dpi
Time to First Page (Black) As fast as	6.5 seconds
Print Speed (Letter, Black): Up to	40 ppm
Print Speed (Letter, Black) Duplex: Up to	18 spm
Print Speed (A4, Black) Duplex: Up to	18 spm
Recommended Monthly Page Volume	1, 500 - 10, 000 pages
Maximum Monthly Duty Cycle: Up to	80, 000 pages per month
Duty Cycle Notes	"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month.
	Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.
	"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.
Noise Level, Idle	inaudible dBA
Print Noise Level, Operating	53 dBA
Duplex Print Noise Level, Operating	52 dBA
Quiet Mode	49 dBA
Processor	466 MHz
Memory, Standard	64 MB
Memory, Maximum	576 MB
Hard Disk	Not Available
Printable Area	0.158 inches of the top, bottom, right and left edges (within)
Printable Area (metric)	4 mm of the top, bottom, right and left edges (within)
Supplies Yield	*Average standard page yield value declared in accordance with ISO/IEC 19752.
	9, 000*-page High Yield Toner Cartridge
	3, 500*-page Toner Cartridge
	18, 000*-page Extra High Yield Toner Cartridge
Photoconductor Estimated Yield: Up to	30, 000 pages, based on 3 average letter/A4-size pages per print job
Cartridge(s) Shipping with Product	7, 000*-page starter Return Program Toner Cartridge

ComX Computers

Product Specification Sheet

Photoconductor Notes	Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.
	Supplies: Functions only with replacement cartridges designed for use in the United States and Canada
	.
Paper Handling Standard	150-Sheet Output Bin
	250-Sheet Drawer
	Integrated Duplex
	Single Sheet Exit
	250-Sheet Input Tray
	50-Sheet Multipurpose Feeder
Number of Paper Inputs, Standard	3
Number of Paper Inputs, Maximum	3
Paper Input Capacity, Standard: Up to	550 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum: Up to	550 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard: Up to	150 pages 20 lb or 75 gsm bond
Paper Output Capacity, Maximum: Up to	150 pages 20 lb or 75 gsm bond
Envelope Capacity	7
Finishing Option	No
Duplex (2-sided) Printing	Integrated Duplex
Media Types Supported	Card Stock
	Envelopes
	Paper Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide

ComX Computers

Product Specification Sheet

Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	9 Envelope
	A4
	A5
	B5 Envelope
	C5 Envelope
	DL Envelope
	A6 Card
	Executive
	Folio
	JIS-B5
	Legal
	Letter
	Statement
	Universal
	Oficio
Network Management Protocols	HTTP
	HTTPs (SSL*/TLS)
	SNMPv3
	WINS
	IGMP
	BOOTP, RARP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	SNMPv2c
	Bonjour
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.

ComX Computers

Product Specification Sheet

Network Printing Methods	LPR/LPD
	Direct IP (Port 9100)
	HTTP
	Enhanced IP (Port 9400)
	FTP, TFTP
	IPP 1.1 (Internet Printing Protocol)
	ThinPrint .print integration
Network Protocol Support	TCP/IP IPv4
	IPX/SPX
	AppleTalk
	LexLink (DLC)
	TCP/IP IPv6
	TCP
	UDP
Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
Microsoft Windows Operating Systems Supported	Microsoft Windows 2000
	Microsoft Windows XP
	Microsoft Windows Server 2003
	Microsoft Windows XP x64
	Microsoft Windows Server 2003 running Terminal Services
	Microsoft Windows 2000 Server running Terminal Services
	Microsoft Windows Server 2003 x64
	Microsoft Windows Server 2003 x64 running Terminal Services
	Microsoft Windows Vista
	Microsoft Windows Vista x64
	Microsoft Windows Server 2008
	Microsoft Windows Server 2008 x64
	Microsoft Windows Server 2008 running Terminal Services
	Microsoft Windows Server 2008 x64 running Terminal Services
	Microsoft Windows 7
Apple Macintosh Operating Systems Supported	Apple Mac OS X (10.2 or later)
	Apple Mac OS 9.2

ComX Computers

Product Specification Sheet

Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0
	Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5
	Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
Linux Operating Systems Supported	Linpus Linux Desktop 9.2, 9.3
	Red Hat Enterprise Linux WS 3.0, 4.0, 5.0
	SUSE Linux Enterprise Server 8.0, 9.0, 10, 11
	SUSE Linux Enterprise Desktop 10
	openSUSE 10.2, 10.3, 11.0, 11.1
	Linspire Linux 6.0
	Debian GNU/Linux 4.0
	Red Flag Linux Desktop 5.0, 6.0
	Ubuntu 7.10
	Ubuntu 8.04 LTS
	SUSE Linux Enterprise Desktop 11
	Debian GNU/Linux 5.0
	Ubuntu 8.10, 9.04
Novell Operating Systems Supported	Novell Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS)
	Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)
UNIX Operating Systems Supported	Sun Solaris SPARC 8, 9, 10
	Sun Solaris x86 10
	HP-UX 11.11, 11.23, 11.31
	IBM AIX 5.2, 5.3, 6.1
Other Operating Systems Supported	IBM iSeries or IBM AS/400 Systems with TCP/IP with OS/400 V3R1 or later using OS/400 Host Print Transform
	Virtually any platform supporting TCP/IP
Standard Ports	Centronics IEEE 1284 Bidirectional Parallel
	USB 2.0 Specification Hi-Speed Certified (Type B)
	Ethernet 10/100BaseTX (RJ-45), also works with 1000Base-T
Optional Network Ports	Lexmark N4050e 802.11g Wireless Print Server (Print Only)
	External MarkNet N7020e Gigabit Ethernet

ComX Computers

Product Specification Sheet

Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
	91 scalable PostScript fonts
Printer Languages (Standard)	PCL 5e Emulation
	PCL 6 Emulation
	Personal Printer Data Stream (PPDS)
	PostScript 3 Emulation
	xHTML
	PDF 1.6
	Direct Image
	Microsoft XPS (XML Paper Specification)
UNSPSC Code	43212105
Display	4-line 160 x 64 pixel All Points Addressable (APA) backlit gray-scale display
Energy Star	Yes
Energy Star Typical Electricity Consumption (TEC)	3.03 kilowatt-hours per week
Size (in. - H x W x D)	13.7 x 15.98 x 14.55 in.
Size (mm - H x W x D)	347 x 406 x 369.5 mm
Weight (kg)	16.6 kg
Packaged Size (in. - H x W x D)	22.6 x 18.1 x 16.5 in.
Packaged Size (mm - H x W x D)	575 x 460 x 420 mm
Packaged Weight (lb.)	40.3 lb.
Packaged Weight (kg)	18.3 kg
Product Certifications	Blue Angel (RAL-UZ-122), FCC Class B, UL 60950-1 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class B, Energy Star, CE Class B, CB
	IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, N Mark, ACA C-tick Class B, CCC Class B, BSMI Class B, MIC, EK Mark, PSB

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/PRLE34S0816-Lexmark-E462dtn-Network-and-Duplex-Ready-Mono-Laser-Printer-p-48993.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-28 15:23:19.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.