

PRLE36S0505

Lexmark MS622de Mono Single Function Printer

Product Overview

Lexmark MS622de Mono Single function Printer, 47 ppm, 1024 MB, USB, Gigabit Ethernet, Wireless, Front USB, Rear USB, Internal Card Slot, Duplex, 100-sheet MPF, 550-Sheet Input



Specifications

Features:

Ready when you are

Robust and reliable, Lexmark printers are built to work anywhere from showroom to warehouse with few interventions. Keep going with long-life components, replacement cartridge yields up to 25,000 pages** and a maximum input capacity of 2300 pages.

The definition of clear text

Some laser printers struggle to print grey text that's easy to read-not the MS620 series. Its innovative font outlining technology makes even the smallest grey text crisp and clear.

Versatile media handling

Print what you want, in the size you want. The included media tray adjusts to paper sizes from A6 to legal, while the 100-sheet multipurpose feeder accepts smaller media and envelopes to give you even more design and output possibilities.

Energy efficiency

Make every watt count with energy management features that reduce power consumption whether the printer is active or in sleep mode. Lower fusing temperature and automatic management of processor cores based on workload help meet rigorous ENERGY STAR 2.0 requirements. That benefits the planet and your budget.

Full-spectrum security

Lexmark's comprehensive approach to product security is a design and engineering mandate across our entire product portfolio. Our security features help keep your information safe-in the document, on the device, over the network, and at all points in between. That's why Keypoint Intelligence-Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***. And this Lexmark product enables you to be GDPR ready.

Performance and value

Get mono printing at up to 50 pages per minute at an affordable price. Also included are two-sided printing and a convenient

ComX Computers

Product Specification Sheet

front USB port for printing files from your thumb drive. Durability and long-life components keep your maintenance costs low, too.

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	PRLE36S0505
--------------	-------------

General Specs

Part no.	36S0519
Print Technology	Monochrome Laser
Workgroup Size	Medium Workgroup
Display	Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, Statement, Executive, Universal, DL Envelope, Folio, 10 Envelope
Included Paper Handling	100-Sheet Multipurpose Feeder, 250-Sheet Output Bin, Integrated Duplex, 550-Sheet Input
Standard Ports	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Size (mm - H x W x D)	303 x 399 x 374 mm
Weight	16.1 kg
Packaged Size (mm - H x W x D)	422 x 430 x 470 mm
Packaged Weight, kg	18.10 kg

Printing

Print Speed	Up to:
	Black: 47 ppm (A4)
Print Speed Duplex	Up to:
	Black: 24 spm (A4)
Time to First Page	As fast as:
	Black: 6 seconds
Print Resolution	Black: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 600 x 600 dpi, 1200 IQ (1200 x 600 dpi)
Duplex	2-sided:
	Integrated Duplex
Printable Area	metric: 4.0 mm of the top, bottom, right and left edges (within)

Paper Handling

Media Types Supported	Paper Labels, Card Stock, Plain Paper, Transparencies, Envelopes, Refer to the Paper & Specialty Media Guide
Finishing Option	No

ComX Computers

Product Specification Sheet

Number of Paper Inputs	Standard: 2
	Maximum: 5
Paper Input Capacity	Standard: 650 pages 75 gsm bond
	Maximum: 2300 pages 75 gsm bond
	650 pages 75 gsm bond
Paper Output Capacity	Up to:
	Standard: 250 pages 75 gsm bond
	Maximum: 250 pages 75 gsm bond
Paper Weight Range Supported	gsm:
	60 - 120 gsm (Standard Tray)
	60 - 216 gsm (Multipurpose Feeder)
Optional Paper Handling	550-Sheet Lockable Tray, 250-Sheet Tray, 550-Sheet Tray
Recommended Monthly Page Volume	2000 - 20000 pages
Maximum Monthly Duty Cycle	Up to:
	175000 pages per month
Cartridges & Imaging	
Laser Cartridge Yields	up to:
	15, 000-page Black High Yield Cartridge
	6, 000-page Cartridge
	20, 000-page Extra High Yield Cartridge
	25,000-page Ultra High Yield Cartridge
Imaging Unit Estimated Yield	Up to:
	60000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product	6, 000-page Return Program Toner Cartridge
Replacement Cartridges	Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.
Hardware	
Processor Speed	Dual Core, 1.0 GHz
Memory	Standard: 1024 MB
	Maximum: 1024 MB
Hard Disk	Option available
Printer Languages	Standard:
	PCL 5e Emulation, PCL 6 Emulation, Microsoft XPS (XML Paper Specification), Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.7 emulation, Direct Image, AirPrint
Fonts and Symbol Sets	2 PCL bitmap fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 84 scalable PCL fonts, 91 scalable PostScript fonts, 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 5 PPDS bitmap fonts, 39 scalable PPDS fonts

ComX Computers

Product Specification Sheet

Touch Screen Display	Yes
Connectivity	
Direct USB	Yes
Ethernet Network	Yes
Wireless	Wireless Option
Network Protocol Support	TCP/IP IPv6, TCP/IP IPv4, TCP, UDP
Network Printing Methods	LPR/LPD, Direct IP (Port 9100), Pull Printing, Microsoft Web Services WSD, Secure IP (Port 96xx), FTP, TFTP, Enhanced IP (Port 9400), ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)
Network Management Protocols	DHCP, APIPA (AutoIP), mDNS, IGMP, Bonjour, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet, NTP, ICMP, HTTP, DNS, ARP, HTTPs (SSL/TLS), Finger
Network Security	IPSec, SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
Optional Local Ports	Internal 1284-B Bidirectional Parallel, Internal RS-232C serial
Optional Network Ports	MarkNet N8230 Fiber Ethernet Print Server, Marknet N8370 WiFi Option, Marknet N8372 WiFi Option
Supported Operating Systems	
Microsoft Windows Operating Systems Supported	Windows 10, Windows Server 2008 x64, Windows 8.1, Windows 8, Windows Server 2008, Windows Server 2008 R2, Windows 8 x64, Windows 7 x64, Windows Server 2012, Windows RT 8.1, Windows XP x64, Windows Server 2003 x64, Windows RT, Windows Server 2003, Windows Server 2012 R2, Windows XP, Windows 8.1 x64, Windows Vista x64, Windows Vista, Windows 7
Apple Operating Systems Supported	Apple OS X (10.5, 10.6, 10.7, 10.8, 10.9, 10.10)
Linux Operating Systems Supported	PCLinuxOS 2011, Ubuntu 11.04, 11.10, 12.04, 12.10, openSUSE 11.3, 11.4, 12.1, 12.2, Linpus Linux Desktop 9.6, Mint 9, 10, 11, 12, 13, Debian GNU/Linux 5.0, 6.0, Fedora 14, 15, 16, 17, Red Hat Enterprise Linux WS 4.0, 5.0, 6.0, SUSE Linux Enterprise Desktop 10, 11, Red Flag Linux Desktop 6.0, SUSE Linux Enterprise Server 10, 11
Citrix MetaFrame	Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64, Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0
Novell Operating Systems Supported	Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell NetWare 6.5 Open Enterprise Server
UNIX Operating Systems Supported	Sun Solaris x86 10, 11, Sun Solaris SPARC 9, 10, 11, IBM AIX 5.3, 6.1, 7.1, HP-UX 11.11, 11.23, 11.31
Electrical & Operation	
ENERGY STAR	Yes
ENERGY STAR Typical Electricity Consumption	TEC:
	2.1 kilowatt-hours per week

ComX Computers

Product Specification Sheet

Noise Level	Operating:
	14 dBA (Idle)
	56 dBA (Print)
Duplex Print Noise Level	Operating:
	56 dBA
Average Power	0.1 watts (Hibernate Mode)
	2.2 watts (Sleep Mode)
	9.5 watts (Ready Mode)
	670 watts (Printing)
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity
	Altitude: 0 - 5000 meters
	Temperature: 10 to 32-Degrees Celcius
Product Certifications	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, China Green Product (CGP)
UNSPSC Code	43212105
Country of Origin	US/Canada/LV LAD - Mexico, LA HV, AP & EMEA - PRC
License/Agreement Terms	Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/prINTERlicense for details.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/PRLE36S0505-Lexmark-MS622de-Mono-Single-Function-Printer-p-256247.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-27 12:33:36.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.