ComX Computers
Product Specification Sheet

PRLE47B1111

Lexmark X79X IPDS Card

Product Overview

Lexmark X79X IPDS Card



Specifications

Overview:

This Card supports AFP/IPDS colour printing from an IBM iSeries, AS/400, IBM zSeries or System/390 computer over TCP/IP to LAN printers.

Features:

AFP/IPDS printing

Print either host-based or client-based output on your network-attached Lexmark laser printer. With a Lexmark Card for IPDS option, use your MFP or printer for both network printing and for IBM iSeries, AS/400, IBM zSeries or System/390 computer jobs.Print bar codes, forms, publications and graphics closer to your end users giving you the associated cost and time savings from true distributed printing. So now direct your colour AFP/IPDS output using the TCP/IP protocol.

Colour Printing

Supports Function Set 45 (FS 45) for full colour printing.

Maximise productivity

Locate your printer wherever you need it to maximise its productivity. With Lexmark's SmartSwitch auto-emulation sensing built into every Lexmark laser printer, your printer will automatically switch to the proper document language, whether it is IPDS, PostScript or PCL . Configure IPDS configuration settings using the MarkNet print server's resident web server, a browser and the printer's IP address.

Notable Features

Host Resource Resolution is sensed (Auto) to enable support for 240, 300 and 600 dpi. Supports 2-dimensional bar codes such as PDF 417, DataMatrix, Maxicode and Quick Response(QR). Supports 1-dimensional bar codes such as Code 128, US Postal bar codes including PLANET and Intelligent Mail Container, Royal Mail bar codes including Red Tag, and other retail and postal bar codes.

Font Capture to Reduce Network Traffic

Using Print Services Facility (PSF), capture fonts (including Chinese, Korean and Japanese), either TrueType, bitmaps or outlines, to hard disk or to flash memory resulting in reduced network traffic.

Consideration

Only one of these cards may be used at any time: Forms and Bar Code, Card for IPDS, Card for PRESCRIBE or Lexmark PrintCryption Card. These cards are installed in the same single connector.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/PRLE47B1111-Lexmark-X79X-IPDS-Card-p-122025.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-16 09:30:41.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.