

RB-BASEBOX5

MikroTik RouterBOARD Basebox 5 RouterBOARD 912UAG - 802.11a/n 2x2 wireless

Product Overview

MikroTik RouterBOARD Basebox 5 RouterBOARD 912UAG - 802.11a/n 2x2 wireless, 600Mhz Atheros CPU, 64MB RAM, 1x Gigabit LAN, USB, 1x miniPCle, Built-in 5Ghz 802.11a/n 2x2 wireless, RouterOS L4, 2x RPSMA connectors for antennas, Antenna not included



Specifications

Features:

- The RB912 in an outdoor enclosure, fit with two RPSMA connectors for antennas, and a cable hood for protection against moisture. Also available are three additional places for antenna connectors, in case you wish to use the RB912 miniPCle slot for one more wireless interface to make a dual band device.
- The case can be opened with one hand, and is protected against the elements. USB, Ethernet and a Grounding wire exits are provided on the bottom, behind a protective door.
- Comes with a mounting loop for tower/pole mounting, and a separate DIN rail mount is also provided. Package also includes a PoE injector
- and power supply unit.
- Box contains: RB912 outdoor unit, PSU, PoE injector, mounting loop, DIN rail mount

Specifications:

ComX Computers

Product Specification Sheet

© 2017 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	RB-BASEBOX5
--------------	-------------

General

Product code	RB912UAG-5HPnD-OUT
Architecture	MIPS-BE
CPU	AR9342
CPU core count	1
CPU nominal frequency	600 MHz
Dimensions	246x135x50mm
License level	4
Operating System	RouterOS
Size of RAM	64 MB
Storage size	64 MB
Storage type	NAND
Tested ambient temperature	-30C to +60C

Powering

Max Power consumption	14W at 24v
Number of DC inputs	1 (PoE-IN)
PoE in	Passive PoE
PoE in input Voltage	8-30 V

Wireless

Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n
Wireless 5 GHz chip model	AR9342

Ethernet

10/100/1000 Ethernet ports	1
----------------------------	---

Peripherals

Number of SIM slots	1
MiniPCI-e slots	1
Number of USB ports	1
USB Power Reset	Yes
USB slot type	USB type A

Other

PCB temperature monitor	Yes
-------------------------	-----

ComX Computers

Product Specification Sheet

Voltage Monitor	Yes
-----------------	-----

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/RB-BASEBOX5-MikroTik-RouterBOARD-Basebox-5-RouterBOARD-Buy-p-172554.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-13 13:29:12.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.