

RCT-10000-WPTU

RCT 10000VA / 8000W Online Tower UPS

Product Overview

RCT 10000VA / 8000W Online Tower UPS, 12 V / 9 Ah batteries x16, Online pure sine-wave UPS, Voltronic Power Winner Pro UPS.



Specifications

Specifications:

CAPACITY	10000 VA / 8000 W
PHASE	Single phase with ground
INPUT	
Input Voltage Range	110-300 VAC (Based on load at 50%); 176-300 VAC (Based on load at 100%)
Nominal Voltage	208/220/230/240 VAC
Frequency Range	46~54 Hz or 56~64 Hz
Power Factor	>= 0.99 @ Nominal Voltage (100% load)
OUTPUT	
Voltage Regulation	+/- 1%
Output Voltage	208/220/230/240 VAC
Frequency Range (Batt. Mode)	50 Hz or 60 Hz +/- 0.1 Hz
Transfer Time : AC Mode to Battery Mode	Zero
Transfer Time : Inverter to Bypass	Zero
Transfer Time : Waveform (Batt. Mode)	Pure Sine Wave
Current Crest Ratio	3::1
Harmonic Distortion	

ComX Computers

Product Specification Sheet

Frequency Range (Synchronized Range)	46~54 Hz or 56~64 Hz
EFFICIENCY	
Battery Mode	0.91
AC Mode	0.93
BATTERY	
Long-run Model : Battery Type	Depending on the capacity of external batteries
Long-run Model : Charging Current (max.)	1A/2A/4A/6A (Adjustable, 6A is only available for 16pcs batteries)
Long-run Model : Charging Voltage	273 VDC +/- 1% (Based on 20pcs bateries)
Long-run Model : Numbers	16~20 (Adjustable)
Standard Model : Battery Type	12 V / 9 Ah
Standard Model : Charging Current (max.)	1A/2A
Standard Model : Charging Voltage	218.4 VDC +/- 1%, 273 VDC +/- 1%
Standard Model : Numbers	16, 20
Standard Model : Typical Recharge Time	9 hours recover to 90% capacity
INDICATORS	
LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators
ALARM	
Battery Mode	Sounding every 4 seconds
Low Battery	Sounding every second
Overload	Sounding twice every second
Fault	Continuously sounding
ENVIRONMENT	
Operating Humidity	0~95% RH @ 0- 40 degreesC (non-condensing)
Noise Level	Less than 58dB @ 1 Meter
PHYSICAL	
Standard Model : Dimension, D x W x H (mm)	442 x 190 x 688
Standard Model : Net Weight (kgs)	66, 76
Long-run Model : Dimension, D x W x H (mm)	442 x 190 x 318
Long-run Model : Net Weight (kgs)	16
MANAGEMENT	
Optional SNMP	Power management from SNMP manager and web browser
Smart RS-232/USB	Supports Windows 2000/2003/XP/Vista/2008, Windows 7/8/10, Linux, and MAC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/RCT-10000-WPTU-RCT-10000VA-8000W-Online-Tower-UPS-Buy-p-184373.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-10 23:59:47.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.