

RF-TP-RB-C

RF elements TwistPort Adaptor for RouterBOARD - Shielded

Product Overview

RF elements TwistPort Adaptor for RouterBOARD - Shielded



Specifications

Overview:

TwistPort Adaptor for RouterBoard

Integrates MikroTik RouterBoard into TwistPort eco-system.

Features:

What is TwistPort Adaptor

TwistPort Adaptor adapts 3rd party radios to RF elements proprietary TwistPort waveguide connector. Integration of the radio is smooth and requires no tools. Making 3rd party radios compatible with TwistPort allows for using the radio with any TwistPort antenna ever made and enable superior performance, noise immunity and network scalability.

Made For RBM11G

TwistPort Adaptor for RouterBoard is compatible with MikroTik RouterBOARD 9XX, 7XX and 4XX series, as well as with the recent M11 Series. Transition to TwistPort waveguide connector is terminated with two MMCX pigtails.

Aluminium Enclosure

TPA-RBC is made of cast aluminium and provides excellent protection that is required in outdoor environment.

ComX Computers

Product Specification Sheet

More Real Estate

TPA-RBC offers more real estate inside the enclosure. It can be used for any additional equipment when building your own radio platform e.g. for radio cards with taller heat sinks.

More Flexibility

TPA-RBC offers space for additional external connectors of choice. Aluminium wall allows for custom drilling or milling to fulfill various requirements.

Excellent Performance

TPA-RBC covers a wideband spectrum of 5180-6100 MHz.

Easy Installation

We are the Champions of Easy. Check out yourself:

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	RF-TP-RB-C
Product ID	TPA-RBC
Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Right Angle MMCX
Materials	Insert - Aluminium Alloy
	Body - Aluminium Alloy
Temperature	-40 degreesC to +60 degreesC (-40 degreesF to +140 degreesF)
Wind Survival	160 km/h
Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
Antenna Compatibility	Any TwistPort™ Compatible Antenna
Radio Compatibility	MikroTik™: RouterBOARD™ RBM11G, RB91x, RB71x, RB411L

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/RF-TP-RB-C-RF-elements-TwistPort-Adaptor-for-RouterBOARD-Buy-p-204925.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-16 03:27:06.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

ComX Computers

Product Specification Sheet

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.