**ComX Computers**
Product Specification Sheet

# RG-ES228GS-P

Reyee 28-port Gigabit Smart Cloud Managed PoE Switch

## Product Overview

Reyee 28-port Gigabit Smart Cloud Managed PoE Switch, RG-ES228GS-P, 26x Gigabit Ports, 2x Gigabit SFP Ports, 24x PoE Ports, 370W Maximum PoE budget, 56 Gbps switching capacity











## Specifications

**Overview:**

**RG-ES228GS-P 28-Port Gigabit Smart Cloud Managed PoE Switch**

Enterprise, Hospitality, Factory, Education, Retails, Surveillance, etc.

- 28-Port Gigabit Managed Switch with 24 PoE+ Ports, 2 RJ45 Ports, 2 SFP Ports
- Cost-Effective Smart Cloud Managed Switches
- IP Camera Recognition, Unique Value for CCTV Network
- Automatic Loop Prevention Ensures Service Continuity
- Lifetime management on Ruijie Cloud at anytime anywhere

**Features:**

**RG-ES228GS-P 28-Port Gigabit Smart Cloud Managed PoE Switch**

- 802.3at / 802.3af
- AbundantApplication Scenarios
- Fanless, Quiet and Green

**Cloud, Make Your Business Easy**

- SON, zero touch provisioning to Cloud
- Configure VLANs on Ruijie Cloud APP
- Monitor switch statistics at anytime anywhere
- Easy maintainance, save onsite time and cost

**Specifications:**

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

| Specifications | |
|---|---|
| **Product Code** | RG-ES228GS-P |
| **Item** | RG-ES228GS-P |
| **10/100/1000Base-T ports** | 26 |
| **1000Base-X SFP ports** | 2 |
| **PoE ports** | 24 |
| **Max. PoE budget** | 370W |
| **Switching capacity** | 56 Gbps |
| **Forwarding rate** | 41.664Mpps |
| **MAC address table** | 8000 |
| **VLAN** | 16 |
| **Dimensions (W x D x H)** | 440 mm x 214.9 mm x 44 mm |
| **Weight (With package)** | 4.0kg |
| **Loop prevention** | Yes |
| **Flow control** | Yes |
| **Port isolation** | Yes |

| | |
|---|---|
| **Broadcast storm suppression** | Yes |
| **Cloud management** | Yes |
| **Power consumption** | <= 391W |
| **Power supply** | 100 - 240V AC, 6A |
| **Fan** | Built-in, lower than 25 degreesC stop running |
| **Port surge** | 4 kV |
| **Operating temperature** | 0 degreesC to 40 degreesC |
| **Operating humidity** | 10% to 90% RH |
| **MTBF** | > 200,000 |

## Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

**Product page:**
**https://www.comx-computers.co.za/RG-ES228GS-P-Reyee-28-port-Gigabit-Smart-Cloud-Managed-PoE-Switch-p-299558.php**

*Images and specifications are provided for reference and are subject to change without notice. E&OE.*

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-12 05:43:01.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.