ComX Computers
Product Specification Sheet

RG-RAP73PRO

Reyee RG-RAP73PRO Wi-Fi 7 BE14000 Tri-band Ceiling Access Point

Product Overview

Reyee RG-RAP73PRO Wi-Fi 7 BE14000 Tri-band Ceiling Access Point, RG-RAP73PRO, 3x 6GHz spatial streams, 3x 5GHz spatial streams, 2x 2.4GHz spatial streams, 13657 Mbps Wireless Data rates, 1x 2.5 Gigabit Port, 1x 10 Gbps Optical Ports (SFP+)









Specifications

Overview:

RG-RAP73Pro, Ruijie Wi-Fi 7 BE14000 Tri-Band Ceiling Access Point

- Next-generation performance with Wi-Fi 7, delivering extra-high wireless speeds
- Ideal for high-density scenarios
- Superior streaming with Wi-Fi 7's exclusive MLO feature
- Enhanced data transmission with 4K-QAM for faster speeds
- Equipped with a SFP+ port, unleashing the full potential of Wi-Fi 7
- Ideal for integrating with Multi-G switches to create a robust network

Features:

- A high-performance Wi-Fi 7 BE14000 Tri-Band ceiling AP
- A balance between performance and design.
- A smooth appearance to hold and install.
- Deployment and management are simplified by Ruijie Cloud.
- Change begins now. Experience a network like never before.

Specifications:

© 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	RG-RAP73PRO
Wi-Fi Protocols	IEEE 802.11a/b/g/n/ac/ax/be
6 GHz Spatial Streams	3 spatial streams, 3x3 MU-MIMO
5 GHz Spatial Streams	3 spatial streams, 3x3 MU-MIMO
2.4 GHz Spatial Streams	2 spatial streams, 2x2 MU-MIMO
Wireless Data Rates	13657Mbps
Dimensions (excluding mounting kits)	220 mm x 220 mm x 45 mm (8.66 in. x 8.66 in. x 1.77 in.)
Weight (excluding mounting kits)	<= 1.1 kg (2.43 lbs.)
Number of 10/100/1000/2500BASE-T Ports	1
Number of 10 Gbps Optical Ports (SFP+)	1
Power Supply	802.3bt/at PoE, 54V/0.55A DC
Power Consumption	< 30W
Operating Temperature	0 degreesC to +40 degreesC (32 degreesF to +104 degreesF)
IP Rating	IP41
Max/Recommended Clients	600/200
Certification	CE, RoHS, FCC, ISED, cTUVus

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/RG-RAP73PRO-Reyee-RG-RAP73PRO-Wi-Fi-7-BE14000-Tri-band-Ceiling-Access-Point-p-320103.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-08 17:04:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.