ComX Computers
Product Specification Sheet

SPK-BT-KAMUT2LW-2.1

K-array Azimut 2.1 Bluetooth & WiFi Speaker White

Product Overview


K-array Azimut 2.1 Bluetooth & WiFi Speaker White, KAMUT2LW, 80W mid-high Speakers : 15W each power handling subwoofer, Analog balanced left 3 pin Phoenix, Right 3 pin Phoenix, Analog unbalanced 3.5mm jack stereo, Optic Fibre optic jack connector, 4x USB 2.0, Bluetooth 4.1 Bluetooth low energy, Network 10/100 Mbps Ethernet (RJ45), Wireless LAN 802.11n











Specifications

Overview:

- A pair of essential design speakers to reproduce the mid-high frequency range
- Sub woofer composed by a 6" cone and a passive radiator for low frequencies
- amplifying module which allows two different kinds of input (RCA and XLR) and volume managing

Features:

Composed of two 10cm-long Lyzard loudspeakers, an ultra-compact Rumble subwoofer, a Kommander amplifier and a covert remote control, the Azimut is not only the most discreet professional audio solution on the market, it was developed with the end user in mind.

The mid-high speakers with four 0.5" long-excursion drivers form ultra-micro line arrays that deliver long throw and homogenous coverage with crystal clear audio.

Paired with the Rumble, the system creates full range frequency response with prodigious output and a virtually invisible profile. Only 10cm deep, the sub provides an extremely powerful low-end that can be easily integrated in its surroundings, including furniture and walls.

The amplifier features two balanced analog inputs, a mini jack input and a fiber optical input working up to 192 kHz. It boasts Bluetooth connectivity and USB ports for files such as WAV, FLAC, MP3 and AAC.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	SPK-BT-KAMUT2LW-2.1
Acoustics	Power Handling Subwoofer: 80W, Mid-high speakers: 15W each
	Impedance Subwoofer: 2ohm, Mid-high speakers: 16ohm)
	Frequency range 45Hz - 19kHz (-10dB)
	SPL 1W/1mt Subwoofer: 87dBSPL, Mid-high speakers: 82dBSPL
	Maximum SPL Subwoofer: 100dBSPL (continuous) - 106dBSPL (peak), Mid-high speakers: 92dBSPL (continuous) - 98dBSPL (peak)
Coverage	Horizontal Subwoofer: omni, Mid-high speakers: 140 degrees
	Vertical Subwoofer: omni, Mid-high speakers: 20 degrees

Crossover	Type Internal digital crossover
Transducers	Low frequency 2 x 4" Ferrite Magnet with 1" voice coil 2 x 4" Passive Radiator
	Mid-High frequency 4 x 0.5" Neodymium Magnet with 0.5" voice coil
Audio Input	Analog Balanced Left: 3-pin phoenix, Right: 3-pin phoenix
	Analog Unbalanced 3.5mm Jack Stereo
	Optic Fibre Optic Jack Connector
	USB 4 x USB 2.0
	Bluetooth 4.1 Bluetooth Low Energy
Power Audio Output	Subwoofer 4-pin phoenix (Ch1-Ch2 PBTL config)
	Mid-high speakers Left: 2-pin phoenix (Ch3 BTL config) Right: 2-pin phoenix (Ch4 BTL config)
Remote	Wired Remote Control 2-pin phoenix
	Hardware Control 5-pin phoenix (4 x GPIO ports)
	Network 10-100 Mbps Ethernet (RJ45), Wirelss LAN 802.11n
DSP Processing	Sample Rate 96 kHz
	Bit Depth 32 bit
Amplifier	Type 4-channel Class-D audio amplifier
	Power 4 x 50W @ 4ohm
	Azimut Config Subwoofer: 100 W @ 2ohm (Ch1-Ch2 PBTL config) Mid-high out left: 50 W @ 4ohm (Ch3 BTL config) Mid-high out right: 50 W @ 4ohm (Ch4 BTL config)
Protection	Type Output Short Protection, DC Offset, Overtemperature, Undervoltage and Overvoltage, 40V Load Dump, Open Ground and Power Tolerant
DC Power	Operating Range 24Vdc - 5A
	Connector 2.5mm power jack
Physical Overview	Dimensions Mid-high: 2.2 x 10.0 x 1.2 cm (0.8"x 3.9"x 0.4") Subwoofer: 50.0 x 11.6 x 10.1 cm (19.7"x 4.6"x 4.0") Amplifier: 14.4 x 4.6 x 14.4 cm (5.7"x 1.8"x 5.7") Remote: 2.2 x 10.0 x 1.2 cm (0.8"x 3.9"x 0.4")
	Weight Mid-high: 0.065 kg (0,14 lbs) Subwoofer: 5.2 kg (11.46 lbs) Amplifier: 0.5 kg (1.10 lbs) Remote: 0.045 kg (0.10 lbs)
	New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from those presented in this catalogue.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/SPK-BT-KAMUT2LW-2-1-K-array-Azimut-2-1-Bluetooth-WiFi-Speaker-White-p-230664.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

ComX Computers

Product Specification Sheet

PDF generated: 2026-11-19 12:19:37.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.