ComX Computers
Product Specification Sheet

SSDPEDMW400G4X1

Intel 750 series 400Gb PCI-e 3.0 (4x) 20nm MLC Solid-State Drive

Product Overview

Intel SSDPEDMW400G401 SSD 750 series, PCI-e 3.0 (4x) with NVMe, 400Gb, 20nm MLC Solid-State Drive, native read: 2200mb/sec / write 900mb/sec, MAX Read/Write 4K: 430000/230000 ioPS, 1.2millions MTBF with 219TB TBW



Specifications

Overview:

Experience the future of storage performance for desktop client and workstation users with the Intel SSD 750 Series. The Intel SSD 750 Series delivers uncompromised performance by utilizing NVM Express over four lanes of PCIe 3.0. With both Add-in Card and 2.5-inch form factors, the Intel SSD 750 Series eases migration from SATA to PCIe 3.0 without power or thermal limitations on performance. The SSD can now deliver the ultimate in performance in a variety of system form factors and configurations.

Specifications:

© 2016 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	SSDPEDMW400G4X1
Capacity	400GB
PCIe	Gen3 x4
Form Factor	2.5-inch Form Factor
	15mm Z-height
	8639-compatible connector
	Add-in Card (AIC) Form Factor
	Half-height, Half-length
	Single slot x4 connector

Performance	Seq R/W: Up to 2400/1200 MB/s3
	4K Random Read: Up to 440K
	4K Random Write: Up to 290K
Latency (average sequential)	Read: 20 us (TYP)
	Write: 20 us (TYP)
Components	Intel 20nm MLC NAND Flash Memory
Operating System Support	Windows 7* 64 bit
	Windows 8* 64 bit
	Windows 8.1* 64 bit
	UEFI* 2.3.1 or later
Reliability	Uncorrectable Bit Error Rate (UBER): 1 sector per 1016 bits read
	Mean Time Before Failure (MTBF): 1.2 million hours
Power	2.5-inch: 3.3V and 12V Supply Rail
	AIC: 3.3V and 12V Supply Rail
	Enhanced power-loss data protection
	Active/Idle (TYP): 25W/4W (TYP)
Compliance	NVM Express* 1.0
	PCI Express* Base Specification Rev 3.0
	SFF 8639 Enterprise SSD Form Factor Version 1.0a
	PCI Express Card Electro-Mechanical* (CEM) Specification Rev 2.0
Certifications and Declarations	UL*, CE*, C-Tick*, BSMI*, KCC*, Microsoft WHQL*, VCCI
Endurance Rating	70 GB Writes Per Day
	Up to 219 TBW (Terabytes Written)
Temperature Specification	Operating:
	AIC: 0 to 55 degrees C
	2.5-inch: 0 to 70 degrees C
	Non-Operating6: -55 to 95 degrees C
	Temperature monitoring
Weight	AIC: up to 195 gm
	2.5-inch: up to 125 gm
Shock	2.5-inch: 1,000 G/0.5msec
	AIC: 50 G Trapezoidal, 170 in/s
Vibration	Operating: 2.17 GRMS (5-700Hz)
	Non-Operating: 3.13 GRMS (5-800Hz)
Altitude (Simulated)	Operating: -1,000 to 10,000 ft
	Non-Operating: -1,000 to 40,000 ft
Product Ecological Compliance	RoHS

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/SSDPEDMW400G4X1-Intel-750-series-400Gb-PCI-e-3-0-4x-20nm-MLC-Solid-State-Drive-p-150482.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-20 04:55:03.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.