ComX Computers
Product Specification Sheet

SUA1000XLI

APC Smart-UPS XL 1000VA USB & Serial 230V UPS

Product Overview

APC Smart-UPS XL 1000VA USB & Serial 230V, line interactive with AVR+power conditioning, 1000VA; with monitoring software, USB+serial interface, with smart slot, support multiple extended-run optional battery pack (SUA24XLBP / UXBP24)



Specifications

Specifications:

Output	
Output Power Capacity	800 Watts / 1000 VA
Max Configurable Power	800 Watts / 1000 VA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Crest Factor	up to 5 : 1
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.83 meters
Input voltage range for main operations	160 - 285V
Input voltage adjustable range for mains operation	151 - 302V

Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement Battery	RBC7
RBC Quantity	1
Extended Run Options	APC Smart-UPS XL 1000VA USB & Serial 230V
Interface Port(s)	
DB-9 RS-232, SmartSlot, USB	Available SmartSlot Interface Quantity
1	Control panel
LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators	Audible Alarm
Alarm when on battery : distinctive low battery alarm : configurable delays	Emergency Power Off (EPO)
Surge Protection and Filtering	
Surge energy rating	320 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Physical	
Maximum Height	216.00 mm
Maximum Width	170.00 mm
Maximum Depth	439.00 mm
Net Weight	27.27 KG
Shipping Weight	29.55 KG
Shipping Height	387.00 mm
Shipping Width	320.00 mm
Shipping Depth	591.00 mm
Color	Black
Units per Pallet	24
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	42.00 dBA

Online Thermal Dissipation	120.00 BTU/hr
Conformance	
Regulatory Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Standard Warranty	2 years repair or replace
Environmental Compliance	RoHS 7b Exemption, China RoHS

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/SUA1000XLI-APC-Smart-UPS-XL-1000VA-USB-Serial-230V-UPS-p-54203.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 05:46:18.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.