ComX Computers
Product Specification Sheet

SUA2200I

APC Smart-UPS 2200VA USB & Serial 230V

Product Overview

APC Smart-UPS 2200VA USB & Serial 230V, line interactive with AVR+power conditioning, 2200VA; with monitoring software, USB+serial interface, with smart slot, with cooling fan.



Specifications

Features:

Availability

- Boost and Trim Automatic Voltage Regulation (AVR): Gives higher application availability by correcting low and high voltage conditions without using the battery (not available on all models).
- Intelligent battery management: Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Power conditioning: Protects connected loads from surges, spikes, lightning, and other power disturbances.
- Temperature-compensated battery charging: Prolongs battery life by regulating the charge voltage according to battery temperature.
- Automatic restart of loads after UPS shutdown: Automatically starts up the connected equipment upon the return of utility power.
- Automatic self-test: Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Disconnected battery notification: Warns when a battery is not available to provide backup power.

Manageability

- Network manageable: Provides remote management of the UPS over the network.
- Audible alarms: Actively let you know if the unit is on battery, if the battery is low or if there is an overload condition.
- LED status indicators: Quickly understand unit and power status with visual indicators.
- Serial Connectivity: Provides management of the UPS via a serial port.
- USB connectivity: Provides management of the UPS via a USB port (not available on all models).
- Disconnected battery notification: Warns when a battery is not available to provide backup power.

Serviceability

- User-replaceable batteries: Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR)
- Hot-swappable batteries: Ensures clean, uninterrupted power to protected equipment while batteries are being replaced

- Predictive failure notification: Provides early-warning fault analysis ensuring proactive component replacement.
- Resettable circuit breakers: Enables a quick recovery from overload events.
- Battery failure notification: Provides early-warning fault analysis on batteries enabling timely preventive maintenance

Adaptability

- Adjustable voltage-transfer points: Maximizes useful battery life by widening the input voltage window or tightening the output voltage regulation.
- Adjustable voltage sensitivity: Provides the ability to adapt the UPS for optimal performance in specific power environments or generator applications.

Safety

- Safety-agency approved: Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment.

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Product Code	SUA2200I
Specifications	
Output	
Output Power Capacity	1980 Watts / 2200 VA
Max Configurable Power	1980 Watts / 2200 VA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Efficiency at Full Load	0.95
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Topology	Line Interactive
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13
	(1) IEC 320 C19
	(2) IEC Jumpers
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20
Schuko CEE 7 / EU1-16P	British BS1363A
Input voltage range for main operations	160 - 285V
Input voltage adjustable range for mains operation	151 - 302V

Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Replacement Battery	RBC55
RBC Quantity	1
Communications & Management	
Interface Port(s)	DB-9 RS-232, SmartSlot
Available SmartSlot Interface Quantity	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional
Surge Protection and Filtering	
Surge energy rating	365 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Physical	
Maximum Height	432.00 mm
Maximum Width	196.00 mm
Maximum Depth	544.00 mm
Net Weight	50.92 KG
Color	Black
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Online Thermal Dissipation	275.00 BTU/hr
Conformance	
Regulatory Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Sustainable Offer Status	
RoHS	Compliant

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/SUA2200I-APC-Smart-UPS-2200VA-USB-Serial-230V-p-69399.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 12:25:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.