ComX Computers
Product Specification Sheet

SWD-8507

Switched 2 way High Surge adaptor

Product Overview

Switched 2 way High Surge adaptor. SWITCHED High Surge Multi Adaptor SA 3 Pin to SA 3 Pin Socket + SANS 164-2 Socket - 1140J











Specifications

The SWITCHED High-Surge 2-Way Multi-Adaptor (Model SWD-8507) combines safety, power, and convenience in a sleek, ergonomic design. Designed for South African three-pin sockets (SANS 164-2), it delivers robust protection against electrical spikes, ensuring your valuable appliances remain unharmed.

Key features include a built-in 1140 Joule surge suppressor, rated for up to**18 000 A total surge current (6 000 A across live and neutral)**, safeguarding against power surges and fluctuations. With a maximum load capacity of 4 000 W at 250 V (16 A per outlet), it easily handles high-demand equipment like kettles, room heaters, and entertainment systems. The dual-switched outlets with safety shutters ensure both efficient control and enhanced protection for your household electrical setup.

Tucked into a compact 105 x 60 x 180 mm and lightweight at just 70 g, this adapter excels in both functionality and portability. Ideal for home, office, or travel use - especially in surge-prone areas.

Key Benefits:

- Superior Surge Protection: 1140 J of absorption & 18 kA total rating defends against spikes.
- Independent Switching: Control each outlet separately for efficient energy use.
- Safety Shutters: Enhanced protection from accidental foreign object insertions.
- High Power Capacity: Supports demanding devices up to 4000 W.
- Compact Design: Minimal footprint, lightweight, ideal for travel or crowded outlets.

Why Choose the SWITCHED SWD-8507?

Compared to basic adaptors, the SWD-8507 offers peace of mind with substantial surge protection, safety shutters, dual-switched outlets, and support for high-load devices. It's a durable and smart upgrade for any home or office in South Africa, especially in areas prone to load-shedding rebound surges.

Specifications:

Model	SWD-8507 High-Surge Multi-Adaptor
Outlets	2 x SA 3-pin (SANS 164-2)
Surge Suppression	1140 Joule energy absorption capacity
Total Surge Current Capacity	18 000 A
Surge Peak Current (Live/Neutral)	6 000 A each
Max Load	4 000 W @ 250 V (16 A per socket)
Safety	Individual switches, integrated safety shutters
Dimensions	105 x 60 x 180 mm
Weight	Approx. 70 g
Voltage Rating	250 V AC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/SWD-8507-Switched-2-way-High-Surge-adaptor-p-325208.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-07 20:32:35.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.