

SYBFXR3RMI

APC symmetra LX 3 battery rack-mount XR frame, 230V

Product Overview

APC SYMMETRA LX 3 BATTERY RACK-MOUNT XR FRAME, 230V, Shipping Weight: 68.00(lbs) 30.92(kilos), Shipping Dimensions: 13.50x 23.60x 38.60(in) 34.30x 59.90x 98.00(cen)



Specifications

Features:

Battery modules connected in parallel

Delivers higher availability through redundant batteries.

Hot-swappable batteries

Ensures clean, uninterrupted power to protected equipment while batteries are being replaced

Plug-and-Play external batteries

Ensures clean, uninterrupted power to the loads when adding extra runtime to the UPS.

User-replaceable batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR)

Modular design

Increases adaptability with an open architecture configurable to any IT environment.

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	SYBFXR3RMI
--------------	------------

Batteries & Runtime

ComX Computers

Product Specification Sheet

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery mounting	Enclosed battery cabinet
Battery manufacturer	Panasonic
Expected Battery Life (years)	41703
Available Battery Module Slots	3
Battery Placement	Battery Cabinet
RBC Quantity	3
Physical	
Net Weight	26.82 KG
Maximum Height	215.00 mm
Maximum Width	472.00 mm
Maximum Depth	686.00 mm
Shipping Weight	30.92 KG
Shipping Width	599.00 mm
Shipping Height	343.00 mm
Shipping Depth	980.00 mm
Rack Height	5U
Color	Black
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-4500 meters
Conformance	
Regulatory Approvals	BSMI, EN 50091-1, EN 50091-2, EN 60950, IEC 60950, VCCI, VDE

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/SYBFXR3RMI-APC-SYMMETRA-LX-3-BATTERY-RACK-MOUNT-XR-Buy-p-121041.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-08 08:20:02.

ComX Computers

Product Specification Sheet

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.