ComX Computers
Product Specification Sheet

TL-POE150S

TP-Link TL-POE150S Single Port PoE Injector

Product Overview

TP-Link TL-POE150S Single Port PoE Injector (48VDC)



Specifications

Overview:

The PoE Injector TL-POE150S fully complies with IEEE 802.3af standard, and can work with all IEEE 802.3af PoE compliant PDs (Powered Devices) or PoE Receiver Adapters, such as TP-LINK's TL-POE10R, or other equivalent product, to expand your network to where there are no power line or outlet, where you wish to fix device such as AP, IP Camera or IP Phone, etc.

Features:

- IEEE 802.3af compliant
- Delivers power up to 100 meters(328.1 feet)
- Auto-determine the necessary power requirements
- Plug-and-Play, requires no configuration
- External power adapter supply

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	TL-POE150S
HARDWARE FEATURES	
Interface	2 10/100/1000Mbps RJ45 Port
	AUTO Negotiation/AUTO MDI/MDIX
	1 48VDC POWER INPUT PORT

Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m)
	EIA/TIA-568 100ohm STP (Max 100m)
	100BASE-TX: UTP category 5, 5e cable (Max 100m)
	EIA/TIA-568 100ohm STP (Max 100m)
	1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Power Supply	15.4W (Max. 48VDC)
LED Indicator	PWR
Dimensions (W x D x H)	3.2*2.1*0.9 in.(80.8*54*24 mm)
SOFTWARE FEATURES	
Basic Function	Compatible With IEEE 802.3af Compliant PDs
	Delivers Power Up To 100 Meters
	Auto-Determine The Necessary Power Requirements
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	Gigabit PoE Injector TL-POE150S
	Power Adapter
	RJ45 Cable
	Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista or Windows 7, MAC OS, NetWare, UNIX or Linux.
Environment	Operating Temperature: 0 degreesC~40 degreesC (32 degreesF~104 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/TL-POE150S-TP-Link-TL-POE150S-Single-Port-PoE-Injector-p-216053.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-07 16:43:24.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.