

TP-VIGI-C330L-4


TP-Link C330L Vigi 3MP Outdoor Bullet Network camera with 4mm lens

Product Overview

TP-Link C330L Vigi 3MP Outdoor Bullet Network camera with 4mm Lens, 30m IR working distance, 3D DNR, DWDR wide Dynamic range, IP67 weatherproof rating, 2304 x 1296 maximum Resolution, H.265+ / H.265 / H.264+ / H.264 Video Compression, BLC / 3D DNR / HLC / SmartIR, 1 region ROI, 1x RJ45 10/100 Mbit Self-Adaptive Ethernet Port, DC Power Port, Human & vehicle classification, Motion detection



SmartVid-Smart Video Enhancement



Specifications

Overview:

VIGI C330I - VIGI 3MP Outdoor IR Bullet Network Camera

- 3MP Super-High Definition: The VIGI C330I camera comes with 3MP - more than enough pixels to pick up some of the more discrete details.
- Human & Vehicle Classification: Distinguishes humans and vehicles from other objects, so you receive more accurate event notifications.
- Smart Detection: Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, obstructs the camera, or removes/abandons objects.
- Smart Video Enhancement: VIGI's professional technologies process videos to greatly improve their quality that is vital to your monitoring, including Smart IR, WDR, 3D DNR, and Night Vision.
- H.265+: Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease

ComX Computers

Product Specification Sheet

network loads, and reduce monitoring costs without sacrificing image quality.

- Waterproof: Reliable IP67 for stable outdoor performance.
- PoE/12V DC: Two types of power supply not only give you more convenience but also make your wiring remarkably easy.
- 2.8/4/6 mm Lens: Whether you need a wide-angle lens to cover enclosed spaces or a higher millimeter lens for longer distances in open spaces, C330I comes with three different lens types to better suit your security needs.
- Flexible Management : Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manger.

Features:

Security NeverShuts Down

3MP Outdoor IR Bullet Network Camera VIGI C330I

- High Definition
- Human&Vehicle Classification
- Smart Detection
- SmartVid
- Night Vision
- Smart Video Coding
- IP67
- 12V DC/PoE
- Remote Monitoring
- ONVIF Ensures Compatibility

3MP Super-High Definition

The VIGI C330I camera comes with 3MP- more than enough pixels to pick up some of the more discrete details.

Human & Vehicle Classification

Integrated AI chips support advanced algorithms to distinguish humans and vehicles from other objects. You can flexibly customize alarm rules to match your monitoring needs and receive more accurate event notifications

Smart Detection

Backed by AI algorithms, the VIGI camera offers more smart detection. You will receive notifications when someone crosses a boundary, enters an area you've set, obstructs the camera, or removes/abandons objects.

- Motion Detection
- Line-Crossing
- Area Intrusion
- Abandoned Object Detection
- Object Removal Detection
- Camera Tampering

SmartVid-Smart Video Enhancement

VIGIs professional technologies process videos to greatly improve their quality that is vital to your monitoring, including Smart IR, WDR, 3D DNR, and Night Vision.

More compression. More savings. Same quality.

Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

**Calculations based on laboratory testing using a 3MP VIGI camera, and an actual performance may vary according to the amount of activity recorded, resolution and other variables.

IP67 for Better Protection

Capable of withstanding temperatures from -30-60 degreesC (-22-140 degreesF), VIGI performs well even in harsh environments with rain and dust.

PoE/12V DC

Two power supply ways not only give you more convenience but also make your wiring remarkably easy.

2.8/4/6 mm lens

Whether you need a wide angle lens to cover enclosed spaces like elevators or a higher millimeter lens for longer distances in open spaces like parking lots, C330I comes with three different lens versions to better suit your security needs.

Flexible Installation Gives You More Convenience.

Find the perfect vantage point by simply securing your camera to the ceiling, wall, or pole.

- Ceiling Mounting
- Wall Mounting
- Pole Mounting

Flexible Management

Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manger.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business youve worked hard to build - whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	TP-VIGI-C330L-4
CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	Color: 0.1 Lux, 0 Lux with IR
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Day/Night/Auto/Schedule-Switch
Lens	2.8 mm/ 4 mm/ 6 mm
Aperture	2.8 mm: F2.2
	4 mm: F2.0
	6 mm: F2.0
Lens Mount	M12
Viewing Angle	2.8mm: 97.8 degrees/52.9 degrees/117.9 degrees(H/V/D)
	4mm: 82.5 degrees/44.9 degrees/99.3 degrees(H/V/D)
	6mm: 51.9 degrees/28.7 degrees/60 degrees(H/V/D)
IR Working Distance	30m
Digital Noise Reduction	3D DNR

ComX Computers

Product Specification Sheet

WDR	DWDR
Weatherproof Rating	IP67
LENS	
Type	Fixed Focal Lens
Focal Length	2.8 mm/4 mm/6 mm
Aperture	2.8mm: F2.2
	4mm: F2.0
	6mm: F2.0
FOV	2.8 mm:
	Horizontal FOV: 97.8 degrees, Vertical FOV: 52.9 degrees, Diagonal FOV: 117.9 degrees
	4 mm:
	Horizontal FOV: 82.5 degrees, Vertical FOV: 44.9 degrees, Diagonal FOV: 99.3 degrees
	6 mm:
	Horizontal FOV: 51.9 degrees, Vertical FOV: 28.7 degrees, Diagonal FOV: 60 degrees
Lens Mount	M12
DORI Distance	2.8 mm:
	Detect: 49 m (161 ft)
	Observe: 20 m (67 ft)
	Recognize: 10 m (32 ft)
	Identify: 5 m (16 ft)
	4 mm:
	Detect: 65 m (214 ft)
	Observe: 27 m (89 ft)
	Recognize: 13 m (43 ft)
	Identify: 7 m (21 ft)
	6 mm:
	Detect: 98 m (321 ft)
	Observe: 41 m (134 ft)
	Recognize: 20 m (64 ft)
	Identify: 10 m (32 ft)
VIDEO	
Max. Resolution	2304 x 1296

ComX Computers

Product Specification Sheet

Main Stream	Frame Rate :
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
	Resolution:
	2304x1296, 2048x1280, 1920x1080, 1280x720
	Note: If the image rotation is set to 90 degrees or 270 degrees, the frame rate only supports up to 20fps.
Sub-Stream	Frame Rate :
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
	Resolution:
	704x576, 640x480, 352x288, 320x240
	Note: If the image rotation is set to 90 degrees or 270 degrees, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264
	Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps
	Sub-Stream: 64 Kbps to 512 Kbps
ILLUMINATOR	
IR LED	Quantity: 2
	Range: 30m
	Wavelength: 850nm
White LED	N/A
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
ANGLE ADJUSTMENT (MANUAL)	
Range	Pan: -90 degrees to 90 degrees
	Tilt: -90 degrees to 90 degrees
IMAGE	
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR
	White Balance, Prevent Overexposure to Infrared Light, HLC Adjustable
	by Client Software, Rotation(90 degrees/270 degrees)
Image Enhancement	BLC/3D DNR/HLC/SmartIR

ComX Computers

Product Specification Sheet

Wide Dynamic Range	DWDR
SNR	>= 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	N/A
Audio Input	N/A
Audio Output	N/A
Audio Compression	N/A
Audio Sampling Rate	N/A
Environment Noise Filtering	N/A
Audio Bit Rate	N/A
NETWORK	
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Network Storage	NAS (NFS, SMB/ CIFS)
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS
	RTSP, NTP, UPnP UDP, SSL/TLS
API	ONVIF
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, VIGI NVR, Web
Web Browser	Google Chrome 57 and above
	Firefox 52 and above
	Safari 11 and above
	Microsoft Edge 91 and above
Cloud	Yes
ONVIF	Yes
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Alarm	N/A
Reset Button	N/A
Power	DC Power Port
Button	-
Video Output	-
On-board Storage	N/A
Built-in Microphone	N/A

ComX Computers

Product Specification Sheet

Built-in Speaker	N/A
Audio	N/A
ALARM AND EVENT MANAGEMENT	
Smart Event	Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection
Basic Event	Motion Detection, Video Tampering Detection, Exception (Illegal Login)
Alarm Linkage	Message Push
Linkage Method	N/A
Output Notification	Message Push
GENERAL	
Package Contents	VIGI Network Camera
	Quick Start Guide
	Waterproof Cable Attachments
	Mounting Accessories
Operating Temperature	-30-60 degreesC
Storage Temperature	-40-60 degreesC
Storage Humidity	95% or Less (Non-Condensing)
Operating Humidity	95% or Less (Non-Condensing)
Dimensions(H X W X D)	174 x 74 x 71 mm
Material	Plastic
General Features	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening
Net Weight	0.2 Kg
Gross Weight	0.35 Kg
Power Consumption	12V DC: Max 5W
	PoE: Class 0
Power Supply	12V DC +/- 5%, 5.5mm Coaxial Power Plug
	PoE (802.3af/at, class 0)
Protection	IP67
Product Dimensions (L x W x H)	174 x 74 x 71 mm
Certifications	CE/BSMI/VCCI/ONVIF
VIDEO/IMAGE	
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264
	Sub-Stream: H.265/H.264

ComX Computers

Product Specification Sheet

Frame Rate & Resolutions	Main Stream:
	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
	Resolution: 2304x1296, 2048x1280, 1920x1080, 1280x720
	Sub-Stream:
	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
	Resolution: 704x576, 640x480, 352x288, 320x240
Max. Resolution	3MP (2304 x 1296)
Video Streaming	Main Stream
	Sub-Stream
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software, Rotation(90 degrees/270 degrees)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Video Bit Rate	64 Kbps to 4 Mbps
Day/Night Switch	Day/Night/Auto/Schedule
SMART FEATURE-SET	
Smart Event	Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Area Entrance Detection, Area Exiting Detection, Abandoned Object Detection, Object Removal Detection, Vehicle Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (Illegal Login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/TP-VIGI-C330L-4-TP-Link-C330L-Vigi-3MP-Outdoor-Bullet-Buy-p-285193.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-12 01:41:47.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.