

U026-20M

Eaton USB 2.0 Active Extension Repeater Cable (A M/F)

Product Overview

Eaton USB 2.0 Active Extension Repeater Cable (A M/F), 20M (65.61 ft.), Order on Request



Specifications

Overview:

- Extends and boosts the signal to any USB device cable without signal loss
- Built-in repeater maintains USB signal quality
- Ideal for connecting USB devices beyond the 16-ft. (4.88 m) USB specification
- Full 480Mbps Transfer rate and backward compatible to USB 1.1
- Plug and Play. Compatible with all major operating systems

Features:

The U026-20M is a 20-meter (65-foot) USB 2.0 active extension cable used to increase the length of a USB device cable beyond the 16-foot cable limitation without signal loss and potential performance problems. The U026-20M is a bus-powered extension cable with a built-in signal booster for regenerating the signal to achieve superior signal quality and data transmission. The overall cable length can be extended up to 131 feet (40 meters) by daisy-chaining two active cables. Standard six-foot (1.8-meter), 10-foot (3.1-meter) or 15-foot (4.6-meter) USB A/B cable to reach the desired distance. Meets or exceeds all USB 2.0 specifications and also supports faster data transfer for legacy USB 1.1 devices. Power capacity is up to 90mA of power to the connected device. (If more than 90mA is required, it will either (i) need to have its own power supply, or (ii) be plugged into a powered USB 2.0 hub (such as U222-004-R).

- Maximum Extension Distance: Daisy-chain up to two 20m cables for a complete distance extension of up to 131-ft. (40 m)
- Error-Free Signal Transfer: Supports error-free data transmission at the high speeds of all your USB 2.0 devices. Legacy USB 1.1 devices also get a speed boost with transfer speeds from 1.5 to 480 Mbps
- Universal Compatibility: The cable is compatible with all computers, devices and cables with USB A connectors. Backward compatible to USB 1.1 (12 Mbps)
- Power Capacity: The U026-20M provides up to 90mA of power to the connected device. If your device requires more than 90mA, it will either (i) need its own power supply, or (ii) be plugged into a powered USB 2.0 hub (such as U222-004-R)
- Premium Cabling: Premium double-shielded foil-and-braid cable provides maximum EMI/RFI protection and superior signal quality
- Gold-Plated Connectors: The U026-20M features gold-plated USB A connectors with gold-plated copper contacts to ensure excellent conductivity The connectors feature integral strain relief for durability and long life

ComX Computers

Product Specification Sheet

- Signal Booster: The built-in signal booster regenerates a USB signal for high quality and long extension distances
- RoHS Compliance: The U026-20M is compliant with RoHS standards
- Plug and Play Convenience: no software to load

System Requirements

- A USB 2.0 port and USB 2.0 device are required to achieve USB 2.0 speeds. A USB 1.1 port and/or device can be used, but you will not be able to achieve USB 2.0 speeds.
- The U026-20M provides up to 90mA of power to the connected device. If more than 90mA is required, it will either (i) need to have its own power supply, or (ii) be plugged into a powered USB 2.0 hub (U222-004-R).

Package Includes

- 20-Meter (65 ft.) USB2.0 A/A Hi-Speed Active Extension / Repeater Cable

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	U026-20M
OVERVIEW	
UPC Code	37332167668
Technology	USB 2.0 (High Speed)
Cable Type	Active
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	USB A (FEMALE)
Connector Style	Straight
PHYSICAL	
Cable Jacket Color	Black
Cable Length (m)	20
Shipping Dimensions (hwd / cm)	23.11 x 26.92 x 0.25
Shipping Weight (kg)	0.68
ENVIRONMENTAL	
Operating Temperature Range	28.4 degrees to 125.6 degreesF (-2 degrees to 52 degreesC)
Storage Temperature Range	-4 degrees to 132.8 degreesF (-20 degrees to 56 degreesC)
Relative Humidity	20 to 80% RH, Non-Condensing
STANDARDS & COMPLIANCE	
Product Compliance	RoHS

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/U026-20M-Eaton-USB-2-0-Active-Extension-Repeater-Cable-Buy-p-315618.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-12 02:57:42.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.