

UB-UF-WIFI6

Ubiquiti Ufiber WiFi 6 GPON CPE with 4 Ethernet Ports

Product Overview

Ubiquiti UF-WIFI6 Ufiber WiFi 6 GPON CPE with 4 Ethernet Ports, 2.488 Gbps downstream, 1.244 Gbps upstream, 1x SC/APC, ITU-G.984 GPON WAN Port, 4x GbE RJ45 LAN Ports, WiFi 802.11ax 5 / 2.4 GHz channels



Specifications

Overview:

Ufiber WiFi6 GPON CPE

SKU: UF-WiFi6-US

The Ufiber WiFi6 GPON CPE (UF WiFi6) is a point-to-multipoint WiFi 6 device that creates high-speed GPON connections capable of reaching a 2.4 Gbps downstream rate and 1.2 Gbps upstream rate. The UF WiFi6 has (4) GbE RJ45 LAN ports and (1) GPON WAN port to connect a local fiber line. It also excels at establishing reliably strong, long-distance fiber links up to 20 kilometers, allowing you to extend your service range and build your customer base.

Features:

- 2x2, high-efficiency WiFi 6
- 2.4 GHz band (2x2 MIMO) with a 300 Mbps radio rate
- 5 GHz band (2x2 MU-MIMO and OFDMA) with a 1.2 Gbps radio rate
- 2.4 Gbps max downstream line rate
- 1.2 Gbps max upstream line rate
- Establishes GPON links up to 20 km
- Powerful Layer 2/3 management features
- (1) GPON WAN port
- (4) GbE RJ45 LAN ports
- Powered with the included power adapter or passive PoE
- Internal WiFi 6 (802.11ax) antennas

Specifications:

ComX Computers

Product Specification Sheet

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	UB-UF-WIFI6
Mechanical	
Dimensions	140.8 x 141.5 x 31.65 mm (5.54 x 5.57 x 1.25")
Weight	415 g (0.99 lb)
Enclosure material	UV-stabilized polycarbonate
Hardware	
Processor	Dual-core MIPS 1004 Kc at 900 MHz
Memory	256 MB RAM
Total non-blocking line rate	2.488 Gbps downstream
	1.244 Gbps upstream
Networking interfaces	(1) SC/APC, ITU-G.984 GPON WAN port
	(4) GbE RJ45 LAN ports
	WiFi 802.11ax 5/2.4 GHz channels
PoE interface	(1) PoE in, 24V passive PoE
Management interface	Ethernet in-band
	PON
Button	Factory-reset
Max. power consumption	11W
Power method	USB-C 5VDC, 3A
	24V passive PoE, 0.5A
Power supply	5VDC, 3A power adapter, 1.5 m cord (included)
	Passive PoE 2-pair (4, 5+, 7, 8-)
Supported voltage range	10 to 30VDC passive PoE
	5VDC adapter
Normal TX range of optical module	0.5 to 5 dBm
Normal RX range of optical module	-8 to -28 dBm
Max. WiFi TX power	
2.4 Ghz	20 dBm
5 Ghz	20 dBm
MIMO	
2.4 Ghz	2 x 2
5 Ghz	2 x 2
Max. WiFi radio rate	

ComX Computers

Product Specification Sheet

2.4 Ghz	300 Mbps
5 Ghz	1.2 Gbps
Antenna Gain	
2.4 GHz	1 dBi
5 GHz	3 dBi
Operating temperature	-15 to 45 degrees C (5 to 113 degrees F)
Operating humidity	10 to 90% noncondensing
Certifications	FCC, IC, CE
LEDs	
PON status	(3) signal LEDs
	All-OFF: bootup
	1x orange: signal too low (< -28 db)
	1x white: signal low (>= -28 db)
	2x white: signal good (>= -25 db)
	3x white: signal strong (>= -11 db)
	1x orange + 2x white: signal too strong (>= -8 db)
	3x orange: no signal
	LEDs alternate between orange + white + orange and a signal strength indicator: No authority
Ethernet	Steady white: link up
	Blinking white: activity
	OFF: link down
Power	White: ON
Software	
Mode	ONU/ONT layer 2/3 Ethernet switch
Services	Web server, telnet, NAT, bridging and routing, firewall features, and application passthrough features
Utilities	Dashboard, monitoring, alarms, and logs
Other	Remote reset, remote reboot, remote firmware upgrade, VLAN support
Security	GEM Port Encryption
Ubiquiti specific features	UBNT Discovery and UISP Mobile app
WiFi standards	802.11 b/g
	WiFi 4/WiFi 5/WiFi 6
Wireless security	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3, TKIP/AES)
Minimum software requirements	Any modern web browser (Google Chrome recommended)
Fiber	
Operating wavelength	1310 nm TX/1490 nm RX

ComX Computers

Product Specification Sheet

Optical interface downstream nominal bit rate	2488.32 Mbit/s
Optical interface upstream nominal bit rate	1244.16 Mbit/s
Physical reach	20 km
Supported Data Rates	
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n (WiFi 4)	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11ac (WiFi 5)	6.5 Mbps to 866.7 Mbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80)
802.11ax (WiFi 6)	8.6 Mbps to 1.2 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/UB-UF-WIFI6-Ubiquiti-UFiber-WiFi-6-GPON-CPE-with-4-Buy-p-267171.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-12 05:43:36.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.