ComX Computers
Product Specification Sheet

UB-USW-FLEX-MINI-2.5G

Ubiquiti UniFi Flex Mini 5 port 2.5GbE Switch

Product Overview

Ubiquiti UniFi Flex Mini 5 port 2.5GbE Switch, USW-Flex-2.5G-5, Can be powered with PoE or a USB-C Adapter, 5x 1/2.5 GbE RJ45 Ports, 25 Gbps switching capacity











Specifications

Overview:

Flex Mini 2.5G USW-Flex-2.5G-5

Compact, 5-port 2.5G switch that can be powered with PoE or a USB-C adapter.

- (4) 2.5 GbE ports
- (1) 2.5 GbE PoE input port for power
- Optional powering with included 5V, 1A USB-C adapter

Note.EU version comes with EU power plug only.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	UB-USW-FLEX-MINI-2.5G
Mechanical	
Dimensions	117.1 x 90 x 21.2 mm (4.6 x 3.5 x 0.8")
Weight	206 g (7.3 oz)
Enclosure material	Polycarbonate
Hardware	
Management interface	Ethernet In-Band
Networking interface	(5) 1/2.5 GbE RJ45 ports
Total non-blocking throughput	12.5 Gbps
Switching capacity	25 Gbps
Forwarding rate	18.6 Mpps
Power method	(1) AC power adapter, 5V DC, 1A
	(1) PoE (PairA 1, 2+ , 3, 6-)(PairB 4, 5+ , 7, 8-)
Power supply	External AC/DC adapter
	UniFi PoE switch
Supported voltage range	AC/DC input: 5V DC
	PoE input: 44-57V DC
Max. power consumption	AC/DC input: 5W
	PoE input: 6.4W
Button	Factory reset
Ambient operating temperature	-20 to 45 degrees C (-4 to 113 degrees F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC
Switching Features	

Layer 2 features	STP / RSTP with priorities and port-level disable
	Port isolation
	Storm control
	Port mirroring
	Multicast / broadcast rate limiting
	Flow control
	Jumbo frames
	Egress rate limit
Layer 3 features	-
LEDs	
System	(1) Blue/white: power
	Blinking white: bootup in progress
	Blinking blue: firmware upgrading
	Steady white: factory defaults , unit is awaiting adoption
	Steady blue: unit is adopted
Ethernet	(5) Green: link/activity
Application Requirements	
UniFi Network	Version 8.4.62 and later

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/UB-USW-FLEX-MINI-2-5G-Ubiquiti-UniFi-Flex-Mini-5-port-2-5GbE-Switch-p-310079.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-21 01:43:24.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.