ComX Computers
Product Specification Sheet

UML-192-90

Bosch UML-192-90 Color LCD Display Monitor (19")

Product Overview

Bosch 19-INCH COLOR LCD MONITOR, 1280 x 1024 RESOLUTION, VGA, DVI, HDMI, CVBS, AUDIO, 120/230VAC, 50/60 HZ



Specifications

Overview:

The Bosch UML-192-90 Color LCD Display Monitor (19"), with a flat color TFT LCD screen panel, delivers high-quality images at a resolution of up to 1280 x 1024 (500TVL) with accurate colors. It offers a high contrast ratio of 800:1, a high brightness rating of 300 cd/m², and a viewing angle of 160 x 160 degrees (H x V), and can automatically adapt to the input resolution of the incoming video signal. It features an analog RGB mode, a Digital DVI input, and an HDMI input for using PCs and digital video units in security applications.

Capable of refreshing at every 5 to 8 milliseconds, the monitor displays crisp and clear images with less smearing and image ghosting in fast moving videos. The fluorescent backlights ensure consistence brightness level by avoiding luminance degradation on the monitor to deliver sharp images, so that you can use the monitor for a longer period without eyestrain or excessive fatigue.

Dot crawl is reduced using the 3D Comb filter to ensure a sharp picture with less noise. De-interlace circuitry converts interlaced video, such as common analog television signals or 1080i format HDTV signals, into a non-interlaced form. While multi-language OSD (On-screen Display) offers intuitive and convenient interface for easy operation, the front panel can be used to make any necessary OSD adjustments.

With the auto switching feature, the LCD monitor can automatically switch to and display an available input signal. It includes VGA input for DVR or PC applications, 2 composite BNC inputs for composite video inputs, and loop-through outputs.

The High-performance LCD Monitor can be mounted on a desktop, wall, or rack and is suitable for use with analog video, digital video recorder (DVR), and PC applications.

Features:

- Flat color TFT LCD screen panel
- Resolution - 1280 x 1024 (500TVL)
- Contrast ratio - 800:1
- Hard coating 3H luminance
- Viewing angle - 160 x 160 degrees (H x V)
- Automatically adapt to the input resolution of the incoming video signal
- Fluorescent backlights ensure consistence brightness level by avoiding luminance degradation on the monitor to deliver sharp images
- 3D Comb filter - reduces dot crawl
- Multi-language OSD (On-screen Display) offers intuitive and convenient interface for easy operation
- Auto switching feature to automatically switch to and display an available input signal
- Includes VGA input for DVR or PC applications, 2 composite BNC inputs for composite video inputs
- Loop-through outputs
- Y/C (S-video) and loop-through video and audio inputs
- Response time - 5ms
- LED life - 50,000 hours
- Can be mounted on a desktop, wall, or rack
- Suitable for use with analog video, digital video recorder (DVR), and for PC applications

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	UML-192-90
Package Weight	19.3 lb
Box Dimensions (LxWxH)	21.0 x 19.0 x 7.0"

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/UML-192-90-Bosch-UML-192-90-Color-LCD-Display-Monitor-19-p-130411.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 16:44:50.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.