

UN-IPC2122LB-SF28-A

Uniview UNV - Ultra H.265 2MP mini fixed mini bullet IP camera with 2.8mm lens

Product Overview

Uniview UNV - Ultra H.265 2MP mini fixed mini bullet IP camera, Metal + plastic, Support up to 30 FPS, No analytics, 2.8mm Lens, IP67, 1/2.8" 2.0 Megapixel Progressive Scan CMOS sensor, 10/100 Mbit Base-TX Ethernet, 2MP (1920x1080) @ 30/25fps, Smart IR, Up to 30m, 2D/3D DNR, 3-axis, Support PoE Power Supply



Specifications

Overview:

UNV - Ultra H.265 - 2MP Mini Fixed Mini Bullet Camera (Metal + Plastic) Now support up to 30 FPS

- High quality image with 2MP, 1/2.8" CMOS sensor
- 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
- Ultra 265, H.265, H.264
- Smart IR, up to 30m (98ft) IR distance
- Day/night functionality
- 2D/3D DNR (Digital Noise Reduction)
- IP67 protection
- Support PoE power supply
- 3-Axis

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	UN-IPC2122LB-SF28-A
Camera	IPC2122LB-SF28-A
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens	2.8mm@F2.0
Angle of View (H)	106.7

ComX Computers

Product Specification Sheet

Angle of View (V)	57.1
Angle of View (O)	115.7
Adjustment angle	Pan: 0 degrees~ 360 degrees Tilt: 0 degrees~ 90 degrees Rotate: 0 degrees~ 360 degrees
Shutter	Auto/Manual, 1 ~ 1/100000s
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON)
	0Lux with IR on
Digital noise reduction	2D/3D DNR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps, 720P (1280*720), Max 30fps
	Sub Stream: D1 (720*576), Max 30fps, 640*360, Max 30fps, 2CIF(704*288), Max 30fps, CIF(352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180 degrees
Dewarping	N/A
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
Client	EZView EZLive
Web Browser	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+

ComX Computers

Product Specification Sheet

Interface	
Network	10/100M Base-TX Ethernet
Certifications	
-	CE: EN 60950-1
Certifications	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V+/-25%, PoE (IEEE 802.3af)
	Power consumption: Max 5.5W
Dimensions (L x W x H)	161 x 63 x 62mm (6.4" x 2.5" x 2.4")
Net Weight	0.27kg (0.60lb)
Material	Metal + Plastic
Working Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Storage Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67
Reset Button	N/A

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/UN-IPC2122LB-SF28-A-Uniview-UNV-Ultra-H-265-2MP-mini-Buy-p-256168.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-18 14:19:51.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.