

UN-IPC2312SB-ADF60KM-I0

Uniview UNV Ultra H.265 P1 2MP LightHunter Fixed Bullet IP Camera with 6mm Lens

Product Overview

Uniview UNV Ultra H.265 P1 2MP LightHunter Fixed Bullet IP Camera with 6mm Lens, 1/2.8" 2.0 Megapixel Progressive Scan CMOS Sensor, 120dB WDR, Up to 80m IR range, Ultra 265 / H.265 / H.264 / MJPEG Video Compression, Up to 8 areas ROI, Triple streams, 2D/3D DNR, Smart IR, HLC, BLC, Digital Defog, People Counting, Motion detection, Micro SD up to 256GB, Built-In Mic, 1/1 alarm I/O, 1x RJ45 10M/100M Base-TX Ethernet



Specifications

Overview:

IPC2312SB-ADF40(60)KM-I0

2MP HD Intelligent 80m IR Fixed Bullet Network Camera

- High quality imaging with 2MP, 1/2.8"CMOS sensor
- 2MP (1920*1080)@30/25fps; 720P (1280*720)@30/25fps
- Ultra 265, H.265, H.264, MJPEG
- Smart intrusion prevention, include cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc. accurately focus on human and, motor vehicle and non-motor vehicle
- Intelligent People Flow Counting and Crowd Density Monitoring
- 120dB true WDR technology enables clear imaging in strong light scene
- Support 9:16 Corridor Mode
- Built-in 2 Mic
- Smart IR, up to 80m (262 ft) IR distance
- Supports 256 G Micro SD card
- IP67 protection
- Support PoE power supply

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

ComX Computers

Product Specification Sheet

Specifications	
Product Code	UN-IPC2312SB-ADF60KM-I0
Item	IPC2312SB-ADF60KM-I0
Camera	
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Minimum Illumination	Colour: 0.001 lux (F1.6, AGC ON)
	0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment angle	Pan: 0 degrees ~ 360 degrees, Tilt: 0 degrees ~ 90 degrees, Rotate: 0 degrees ~ 360 degrees
WDR	120dB
S/N	>52dB
Lens	
Lens	6.0mm@F1.6
Iris	Fixed
Field of View (H)	54.2 degrees
Field of View (V)	28.9 degrees
Field of View (D)	61.5 degrees
DORI	
DORI Distance	[1] Lens (mm) [2] Detect (m) [3] Observe (m) [4] [5] Recognize (m)
	[1] 4 [2] 62.1 [3] 24.8 [4] [5] 12.4
	[1] 6 [2] 93.1 [3] 37.2 [4] [5] 18.6
Illuminator	
IR Range	Up to 80m (262 ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps, 720P (1280*720), Max 30fps
	Sub Stream: 720P (1280*720), Max 30fps, D1 (720*576), Max 30fps, 640*360, Max 30fps, 2CIF(704*288), Max 30fps, CIF(352*288), Max 30fps
	Third Stream: D1 (720*576), Max 30fps, 640*360, Max 30fps, 2CIF(704*288), Max 30fps, CIF(352*288), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
U-code	Support
OSD	Up to 8 OSDs

ComX Computers

Product Specification Sheet

Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Video Stream	Triple streams
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal / Vertical / Horizontal / 180 degrees / 90 degreesClockwise / 90 degreesAnti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported
Defog	Digital Defog
Intelligent	
Smart intrusion prevention	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection
Statistical Analysis	People counting, support people flow counting and crowd density monitoring
Events	
Basic Detection	Motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication
Audio	
Audio Compression	G.711
Audio Bitrate	64 Kbps
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS)
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, digest authentication for ONVIF

ComX Computers

Product Specification Sheet

Client	EZStation
	EZView
	EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Interface	
Audio I/O	N/A
Alarm I/O	1/1
RS485	N/A
Built-in Mic	Support 2
Built-in Speaker	N/A
WIFI	N/A
Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
Certifications	
EMC	CE-EMC (EN 55032: 2015+A1:2020, EN 61000-3-3: 2013+A1: 2019, EN IEC 61000-3-2: 2019+A1: 2021, EN 55035: 2017+A11:2020)
	FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Safety	CE LVD (EN 62368-1:2014+A11:2017)
	CB (IEC 62368-1:2014)
	UL (UL 62368-1, 2nd Ed, Issue Date: 2014-12-01)
Environment	CE-RoHS (2011/65/EU, (EU)2015/863), WEEE (2012/19/EU), Reach (Regulation (EC) No 1907/2006)
Protection	IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)
General	
Power	DC 12V+/-25%, PoE (IEEE 802.3af)
	Power consumption: Max 7.0 W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (L x W x H)	206 x 74 x 74mm (8.1" x 2.9" x 2.9")
Weight	0.51kg (1.12lb)
Material	Metal
Working Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Storage Environment	-30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF), Humidity: <=95% RH (non-condensing)
Surge Protection	4KV
Reset Button	Supported

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/UN-IPC2312SB-ADF60KM-I0-Uniview-UNV-Ultra-H-265-P1-Buy-p-285678.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 03:07:27.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.