ComX Computers
Product Specification Sheet

UP-ABCS325N

Back-UPS CS 325 without auto shutdown software, 230V

Product Overview

APC Back-ups CS BK325i, off-line, 350VA - No software + interface



Specifications

Features:

- Data line surge protection: Protects connected loads from surges, spikes, lightning, and other power disturbances.
- Battery-protected and surge-only outlets: Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment
- LED status indicators: Quickly understand unit and power status with visual indicators.
- Audible alarms: Provides notification of changing utility power and UPS conditions.
- Transformer-block spaced outlets: Protect equipment with input transformer blocks without blocking access to other receptacles.
- Automatic self-test: Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Battery replacement without tools: Allows quick, easy battery replacement.
- Cold-start capable: Provides temporary battery power when the utility power is out.
- Hot-swappable batteries: Ensures clean, uninterrupted power to protected equipment while batteries are being replaced
- Automatic restart of loads after UPS shutdown: Automatically starts up the connected equipment upon the return of utility power.
- Resettable circuit breakers: Enables a quick recovery from overload events.

Specifications:

Output	
Output Power Capacity	210 Watts / 350 VA
Max Configurable Power	210 Watts / 350 VA
Nominal Output Voltage	230V
Output Connections	(1) IEC 320 C13 (Surge Protection)
Input	
Nominal Input Voltage	230V

Input Frequency	50/60 Hz +/- 5 Hz (manual switch)
Input Connections	IEC-320 C14
Input voltage range for main operations	196 - 280V
Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6 hour(s)
Replacement Battery	RBC2, RBC2J
RBC Quantity	1
Control panel	
LED status display with On Line : On Battery : Replace Battery and Overload indicators	Audible Alarm
Surge Protection and Filtering	
Surge energy rating	320 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Physical	
Maximum Height	165.00 mm
Maximum Width	91.00 mm
Maximum Depth	284.00 mm
Net Weight	5.73 KG
Shipping Weight	6.73 KG
Shipping Height	178.00 mm
Shipping Width	241.00 mm
Shipping Depth	368.00 mm
Color	Beige
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	40.00 dBA
Online Thermal Dissipation	19.00 BTU/hr
Conformance	

Regulatory Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Standard Warranty	2 years repair or replace
Environmental Compliance	RoHS

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/UP-ABCS325N-Back-UPS-CS-325-without-auto-shutdown-software-230V-p-37949.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 08:25:59.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.