ComX Computers
Product Specification Sheet

UP-ABRS900Gi

APC Back-ups RS BR900Gi

Product Overview

APC Back-ups RS BR900Gi, line interactive with AVR+power conditioning, with LCD graphics display, 900VA, RJ-11 modem/fax + RJ-45 UTP protection; with monitoring software, USB interface



Specifications

Specifications:

Output	
Output Power Capacity	540 Watts / 900 VA
Nominal Output Voltage	230V
Efficiency at Full Load	0.81
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) IEC 320 C13 (Battery Backup)
(4) IEC 320 C13 (Surge Protection)	(2) IEC Jumpers (Battery Backup)
Efficiency at Half Load	0.87
Bypass	Built-in Bypass
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	175 - 295V
Maximum Input Current	8A
Input Breaker Capacity	10.0 A
Batteries & Runtime	

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8 hour(s)
Replacement Battery	APCRBC123
RBC Quantity	1
Interface Port(s)	
USB	Control panel
Multi-function LCD status and control console	Audible Alarm
Surge Protection and Filtering	
Surge energy rating	600 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector)
Physical	
Maximum Height	250.00 mm
Maximum Width	100.00 mm
Maximum Depth	382.00 mm
Net Weight	10.72 KG
Shipping Weight	11.70 KG
Shipping Height	337.00 mm
Shipping Width	225.00 mm
Shipping Depth	487.00 mm
Master Carton Weight	24.00 KG
Color	Black
SCC Codes	1073130427959 1
Units per Pallet	32
Pallet Weight	393.28 KG
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Conformance	

Regulatory Approvals	A-tick, CE, GOST, GS Mark
Standard Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
Environmental Compliance	RoHS, REACH: Contains No SVHCs

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/UP-ABRS900Gi-APC-Back-ups-RS-BR900Gi-p-39309.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 11:59:21.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.