
**ComX Computers**
Product Specification Sheet

# UP-ASSC1500T2U

APC Smart-UPS SC SC1500i

## Product Overview

APC Smart-UPS SC SC1500i, Tower or 2U rackmount, line interactive with AVR+power conditioning, 1500VA, RJ-11 modem/fax + RJ-45 UTP protection; with monitoring software, serial interface



## Specifications

**Specifications:**

| | |
|---|---|
| Output | |
| Output Power Capacity | 865 Watts / 1500 VA |
| Max Configurable Power | 865 Watts / 1500 VA |
| Nominal Output Voltage | 230V |
| Output Voltage Distortion | Less than 5% at full load |
| Output Frequency (sync to mains) | 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal |
| Crest Factor | up to 5 : 1 |
| Waveform Type | Stepped approximation to a sinewave |
| Output Connections | (4) IEC 320 C13 |
| Input | |
| Nominal Input Voltage | 230V |
| Input Frequency | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections | IEC-320 C14 |
| Cord Length | 1.83 meters |
| Input voltage range for main operations | 186 - 284V |
| Input voltage adjustable range for mains operation | 175 - 297V |
| Batteries & Runtime | |

| | |
|---|---|
| Battery Type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
| Typical recharge time | 8 hour(s) |
| Replacement Battery | RBC59 |
| RBC Quantity | 1 |
| Control panel | |
| LED status display with On Line : On Battery : Replace Battery and Overload indicators | Audible Alarm |
| Surge Protection and Filtering | |
| Surge energy rating | 445 Joules |
| Filtering | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449 |
| Data Line Protection | RJ-45 Modem/Fax/DSL/10-100 Base-T protection |
| Physical | |
| Maximum Height | 89.00 mm |
| Maximum Width | 432.00 mm |
| Maximum Depth | 463.00 mm |
| Rack Height | 2U |
| Net Weight | 21.36 KG |
| Shipping Weight | 24.55 KG |
| Shipping Height | 254.00 mm |
| Shipping Width | 610.00 mm |
| Shipping Depth | 610.00 mm |
| Master Carton Units | 1 |
| Color | Grey |
| Units per Pallet | 10 |
| Environmental | |
| Operating Environment | 0 - 40 degreesC |
| Operating Relative Humidity | 0 - 95% |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -5 - 45 degreesC |
| Storage Relative Humidity | 0 - 95% |
| Storage Elevation | 0-15000 meters |
| Audible noise at 1 meter from surface of unit | 45.00 dBA |
| Online Thermal Dissipation | 180.00 BTU/hr |
| Conformance | |
| Regulatory Approvals | C-tick, CE, GOST, VDE |

| | |
|---|---|
| Standard Warranty | 2 years repair or replace |
| Environmental Compliance | RoHS 7b Exemption, China RoHS |

## Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

**Product page: https://www.comx-computers.co.za/UP-ASSC1500T2U-APC-Smart-UPS-SC-SC1500i-p-37962.php**

*Images and specifications are provided for reference and are subject to change without notice. E&OE.*

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 03:51:47.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.