ComX Computers
Product Specification Sheet

UPAPBX500CI

APC BX500CI 500VA Back-UPS with AVR

Product Overview

APC Back-UPS 500VA, 300W, AVR, IEC outlets, EU Medium





Specifications

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	UPAPBX500CI
Main	
Run time for load 300W	1min 20s
Main Input Voltage	230 V
rated power in W	300 W
rated power in VA	500 VA
nb of power socket outlets	3 IEC 60320 C13
	1 IEC Jumpers
cable length	1.83 m
number of cables	1
General	
provided equipment	user manual
product web sub-family	Entry level
Number of power module free slots	0

Number of power module filled slots	0
redundant	No
Physical	
colour	Black
height	18.5 cm
width	11.5 cm
depth	21.3 cm
net weight	5.2 kg
mounting support	Desktop
mounting preference	No preference
mounting mode	Not rack-mountable
two post mountable	0
USB compatible	No
Input	
network frequency	45...65 Hz
input voltage limits	160...280 V
maximum input current	2A
switching current capacity	7A
Output	
Maximum configurable power in W	300 W
output frequency	50 Hz sync to mains
	50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	500 VA
Transfer time	6 ms typical : 10 ms maximum
Conformance	
product certifications	CE
Environmental	
ambient air temperature for operation	0...40 degreesC
relative humidity	0...95 %
operating altitude	0...10000 ft
ambient air temperature for storage	-15...45 degreesC
storage Relative Humidity	0...95 %
storage altitude	0.00...15240.00 m

acoustic level	45 dBA
Batteries & Runtime	
number of battery filled slots	0
number of battery free slots	0
battery voltage	12 V
battery capacity	6.4 Ah
battery charger power	4700 W rated
Battery power in VAH	47 VAh runtime
extended runtime	0
Communications & Management	
control panel	LED status display with on line : on battery : replace battery and overload indicators
alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rate	273 J

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/UPAPBX500CI-APC-BX500CI-500VA-Back-UPS-with-AVR-p-273338.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 18:55:51.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.