ComX Computers
Product Specification Sheet

UPAPEPDU1116S

APC Easy Rack PDU

Product Overview

APC Easy Rack PDU, Switched, 0U, 1 Phase, 3.7kW, 230V, 16A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet



Specifications

Overview:

APC Easy Switched Rack PDU EPDU1116S is Easy-to-install and easy-to-use PDU, making rack power distribution easy and intelligent. This provides on/off outlet switching, advanced power management, load monitoring and much more features than the average power strip. EPDU1116S has IEC 60309 16A 2P+E type inlet, twenty IEC C13 and four IEC C19 type outlet sockets. This is vertical rack mountable PDU in ultra light weight and smart, multifunctional new designed display. Easily mounts vertically in racks or enclosures and occupies zero U of valuable rack space, which allows more equipment in the rack. Remotely manage outlets so users can turn outlets off that are not in use (prevent overloads) or recycle power to locked-up equipment (minimize costly downtime and avoid travel time to equipment) Full-featured network management interfaces that provide standards-based management via Web, SNMP, and Command Line Interface. Allows users to access, configure, and manage units from remote locations to save valuable time. Quickly and easily upgrade firmware via network download for future product enhancements. Eliminates the need to replace products already installed in the field when new features are released. Connect and manage multiple PDUs from one IP address to simplify and speed deployment while saving the cost required in having a dedicated network connection for each PDU Quickly and easily upgrade firmware via network download for future product enhancements. Eliminates the need to replace products already installed in the field when new features are released. Allows users to configure the sequence in which power is turned on or off for each outlet. This helps avoid in-rushes at start-up, which can cause overloaded circuits and dropped loads Sequencing also allows users to predetermine which piece of equipment is turned on first so other equipment dependant on that unit will function properly. Indicates overload and warning conditions based on the user-defined alarm thresholds. Alerts users of potential overloaded circuits. The packaging includes cable, installation guide and horizontal mounting brackets for quick and easy mounting in the enclosure.

Features:

- Reliable and affordable Rack Power Distribution
- Remote individual outlet control capabilities
- Network management capabilities and flash upgradeable
- Network Port Sharing and Outlet Power Sequencing
- Local Current Monitoring Display and Zero U Rack Mounting Abilities

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	UPAPEPDU1116S
Main	
Main Input Voltage	200 V
	208 V
	230 V
PDU type	Switched
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 2P + E
Number of rack unit	0U
Cable length	3.00 m
Number of cables	1
Provided equipment	Installation guide
	User manual
	Vertical mounting brackets
Physical	
Colour	Black
Height	173.8 cm
Width	5.5 cm
Depth	6.2 cm
Net weight	7.3 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical
Input	
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Output	
Number of power socket outlets	20 IEC 60320 C13
	4 IEC 60320 C19
Conformance	

Product certifications	CE
	EAC
	TÜV
Environmental	
Ambient air temperature for operation	-5...45 degreesC
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 degreesC
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	195 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	8.5 kg

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/UPAPEPDU1116S-APC-Easy-Rack-PDU-p-279158.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-05 03:57:00.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.