UPAPSRT8KXLI

APC Smart-UPS SRT 8000VA 230V with SNMP card

Product Overview

APC Smart-UPS SRT 8000VA 230V, Includes SNMP card. Output Voltage : 230, Shipping Weight : 279.00(lbs) 126.82(kilos), Shipping Dimensions : 18.15x 23.62x 39.37(in) 46.10x 60.00x 100.00(cent), Units Per Pallet : 1, UPC Code : 731304304319





Specifications

Features:

LCD graphics display
Text and mimic diagrams that display modes of operation, system parameters and alarms.

10/100 BaseT Connection
Connect the device to a network using a 10 or 100 BaseT connection

Green mode
Patent-pending operating mode that bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection.

Battery failure notification
Provides early-warning fault analysis on batteries enabling timely preventive maintenance

Specifications:

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	SRT8KXLI
Output	
Output Power Capacity	8000 Watts / 8000 VA
Max Configurable Power	8000 Watts / 8000 VA

Nominal Output Voltage	230V
Output Voltage Distortion	Less than 3%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Crest Factor	3:1
Topology	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 3-wire (H N + G)
	(6) IEC 320 C13
	(4) IEC 320 C19
	(3) IEC Jumpers
Bypass	Internal Bypass (Automatic and Manual)
Input	
Nominal Input Voltage	230V, 400V 3PH
Input Frequency	45 - 65 Hz (auto sensing)
Input Connections	Hard Wire 3 wire (1PH+N+G)
	Hard Wire 5-wire (3PH + N + G)
Other Input Voltages	220, 240, 380, 415
Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	1.50 hour(s)
RBC Quantity	2
Communications & Management	
Interface Port(s)	Contact Closure, RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB
Available SmartSlot Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Surge Protection and Filtering	
Surge energy rating	480 Joules
Physical	
Maximum Height	432.00 mm
Maximum Width	263.00 mm
Maximum Depth	715.00 mm
Net Weight	111.82 KG
Shipping Weight	126.82 KG

Shipping Height	461.00 mm
Shipping Width	600.00 mm
Shipping Depth	1000.00 mm
Color	Black
Environmental	
Operating Environment	0 - 40 degreesC
Operating Relative Humidity	0 - 95% no%
Operating Elevation	0-900 meters
Storage Temperature	-15 - 45 degreesC
Storage Relative Humidity	0 - 95% no%
Storage Elevation	0-4500 meters
Audible noise at 1 meter from surface of unit	55.00 dBA
Online Thermal Dissipation	1497.00 BTU/hr
Protection Class	IP 20
Conformance	
Regulatory Approvals	CE, CE Mark
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	Contains Lithium Coin Cell

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/UPAPSRT8KXLI-APC-Smart-UPS-SRT-8000VA-230V-with-SNMP-card-p-100363.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 03:19:53.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.