ComX Computers
Product Specification Sheet

UPAPSRTL3KRM1UIC

APC Smart-UPS Ultra 3000VA 230V 1U UPS with SmartConnect

Product Overview

APC Smart-UPS Ultra, 3000VA 230V 1U, with Lithium-Ion Battery, with SmartConnect



Specifications

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	UPAPSRTL3KRM1UIC
Overview	
Presentation	Ultra high density on-line power protection with scalable runtime supported by Lithium-Ion batteries.
Main	
Run time for load 3000W	4min 37s
Max. Capacity Used	100%
Main Input Voltage	230 V
Other Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	230 V
rated power in W	3000 W
Rated power in VA	3000 VA

Input Connection Type	BS1363A British
	IEC 60320 C20
	Schuko CEE 7 / EU1-16P
output connection type	3 IEC 60320 C13
	2 IEC 60320 C19
Number of rack unit	1U
Cable length	2.44 m
Number of cables	1
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	RJ45 cable
	USB cable
	Safety guide
	Rack mounting brackets
	Rack mounting support rails
	Wall mounting brackets
	Stabilization feet
	Screws
Batteries & Runtime	
Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	50 V
Battery charger power	448 W
Battery design life	8...10 year(s)
Battery power in VAH	336 VAh runtime
Battery option	SRTL50RMBP1U-LI 1 1240 VAh
	SRTL50RMBP1U-LI 2 2471 VAh
	SRTL50RMBP1U-LI 3 3706 VAh
	SRTL50RMBP1U-LI 4 4944 VAh
	SRTL50RMBP1U-LI 5 6192 VAh
Extended runtime	1
General	
product web sub-family	High density
Redundant	No
Physical	
Colour	Silver grey
Height	43 mm

Width	432 mm
Depth	560 mm
Product weight	15.9 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
	Tower-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal
	Vertical
Input	
Network frequency	50/60 Hz auto-sensing
Input voltage limits	160...275 V adjustable (half load)
Output	
Maximum configurable power in W	3000 W
Output frequency	50/60 Hz /- 3 Hz sync to mains
Crest factor	3::1
UPS type	On-Line
Wave type	Sine wave
bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	3000 VA
Conformance	
Product certifications	CE
	UKCA
Marking	CE Mark
	UKCA
Standards	EN/IEC 62040-1
Environmental	
Ambient air temperature for operation	0...40 degreesC
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 degreesC
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

Communications & Management	
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.8 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.2 kg

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/UPAPSRTL3KRM1UIC-APC-Smart-UPS-Ultra-3000VA-230V-1U-UPS-with-SmartConnect-p-282362.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-20 16:39:16.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.