ComX Computers
Product Specification Sheet

VE901R

Aten VE901R DisplayPort HDBaseT-Lite Receiver

Product Overview

Aten VE901R DisplayPort HDBaseT-Lite Receiver (4K@40m; 1080p@70m)





Specifications

Overview:

The VE901R DisplayPort HDBaseT-Lite Receiver is able to extend a DisplayPort display up to 70 m using a Cat 6/6a/ATEN 2L-2910 Cat 6 cable. This combination of ATEN and HDBaseT™ technology supports sharing 4K media up to 40 m away, offering a simple, adaptable, and cost-effective solution for any professional A/V installation.

The VE901R DisplayPort HDBaseT-Lite Receiver is the perfect choice for professional A/V installations that require video signal interference protection, such as in medical and military installations. With its lightweight and easy-to-mount design, and a slip-resistant DC Jack lock mechanism, the VE901R can be installed in a multitude of locations while ensuring peace of mind with its reliability.

Features:

- HDBaseT Connectivity - extends a DisplayPort connection up to 70 meters via a single Cat 6a cable or ATEN 2L-2910 Cat 6 cable
- DisplayPort v1.1*; HDCP 1.4 compliant
- Superior video quality - 4K @ 35 m (Cat 5e/6) / 40 m (Cat 6a/ATEN 2L-2910 Cat 6 cable) and 1920 x 1080 @ 60m (Cat 5e/6) / 70m (Cat 6a/ATEN 2L-2910 Cat 6 cable)
- HDBaseT Anti-Jamming - resists signal interference during video transmission using HDBaseT technology
- Featuring 3.3V / 500mA power output for powering auxiliary devices
- Plug-and-play
- Rack-Mountable

***Note:**DisplayPort v1.1 supports up to 4Kx2K @ 30Hz.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	VE901R
Video Output	
Interfaces	1 x DisplayPort Female (Black)
Impedance	100 ohm
Video	
Max. Data Rate	10.2Gbps (3.4Gbps per lane)
Max. Pixel Clock	297 MHz
Compliance	DisplayPort (Deep Color, 4K)
	HDCP Compatible
Max. Resolutions / Distance	Up to 4K@35m (Cat 5e/6) / 40m (Cat 6a/ATEN 2L-2910 Cat6);
	1080p@60m (Cat 5e/6) / 70m (Cat 6a//ATEN 2L-2910 Cat6)
	*4K supported:
	4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)
Audio	
Input	N/A
Output	1 x DisplayPort Female (Black)
Connectors	
Power	1 x DC Jack (Black) with locking
Unit To Unit	1 x RJ-45 Female
Power Consumption	DC5V:5.72W:27BTU
Environmental	
Operating Temperature	0-40 degreesC
Storage Temperature	-20 - 60 degreesC
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.27 kg (0.59 lb)
Dimensions (L x W x H) with bracket	9.77 x 8.70 x 3.00 cm
	(3.85 x 3.43 x 1.18 in.)
Dimensions (L x W x H) without bracket	9.42 x 6.60 x 2.90 cm
	(3.71 x 2.6 x 1.14 in.)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/VE901R-Aten-VE901R-DisplayPort-HDBaseT-Lite-Receiver-p-295038.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-07 06:58:08.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.