

VER-VOR-ORM-XT

Veracity Outreach Max GXT - PoE in - GbE PoE out external IP66

Product Overview

Veracity Outreach Max GXT - PoE in - GbE PoE out external IP66, VOR-ORM-XT, Extends Cable Range Beyond 100m, Independently Auto-Configuring Port, Extends PoE to Connected Device, Up to 70W PoE Power



Specifications

Overview:

The OUTREACH Max XT Ethernet Extender from Veracity extends the Ethernet network connection and PoE power to non-network units beyond the 100m limit. Encased in an IP66-rated housing for use outdoors, this Ethernet extender comes with a network port that can be configured automatically for network speed, duplex, and crossover. Capable of restoring the network connection every 100m, it maintains 200Mbps bandwidth of regular full-duplex 100Base-T Ethernet. This extender provides PoE to all connected devices up to 70W and is suitable for use in 48-56V PoE applications.

Features:

- Extends Cable Range Beyond 100m
- Independently Auto-Configuring Port
- Extends PoE to Connected Device
- Up to 70W PoE Power
- Restores Network Connection Every 100m
- Full Unrestricted Network Bandwidth
- 10/100Base-T Speeds
- For 48-56V PoE Applications
- IP66-Rated for Outdoor Use

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	VER-VOR-ORM-XT
Power Consumption	1.3 W via PoE

ComX Computers

Product Specification Sheet

PoE Standard	IEEE 802.3af PoE, IEEE 802.3at PoE Plus (two-event signature)
	Custom PoE always-on 48V and 4-pair
PoE Power	Up to 70 watts depending on standard
	Maximum current 0.7 A on data pairs
	Maximum current 1.5 A on spare pairs
Range	Up to 656' (200 m)
Network	10Base-T, 100Base-TX, full/half duplex (auto-negotiated)
	Patch or crossover cables
LED Indicators	Power, network link/activity
Mounting	2/4 x 0.28" (7 mm) holes
Ambient Temperature	-40 to 140 degreesF (-40 to 60 degreesC)
Humidity (Non-Condensing)	Up to 85%
Dimensions (LxWxH)	With Connectors: 8.26 x 2 x 1.2" (210 x 50 x 31 mm)
	Without Connectors: 4.9 x 2 x 1.2" (125 x 50 x 31 mm)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/VER-VOR-ORM-Xt-Veracity-Outreach-Max-GXT-PoE-in-Buy-p-215254.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 01:22:08.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.