

VIVOTEK AW-GET-050A-065

Vivotek unmanaged 4x Gigabit PoE + 1x Gigabit PoE Switch

Product Overview

Vivotek unmanaged 4x Gigabit PoE + 1x Gigabit PoE Switch, AW-GET-050A-065, 5x Gigabit Ethernet (RJ45), 4 PoE out ports, Per Port 56VDC Maximum 30W PoE power Output, 60 W total PoE power budget



Specifications

Overview:

AW-GET-050A-065 - Unmanaged 4xGE PoE + 1xGE Switch

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	VIVOTEK AW-GET-050A-065
Model	AW-GET-050A-065
IP Camera Compatibility	
Video Resolution	Megapixel/D1/VGA
Video Compression	MJPEG/MPEG-4/H.264/H.265
Compatible Camera List	VIVOTEK Network Cameras
Ethernet	
Gigabit Ethernet (RJ45)	5
Standards	
IEEE 802.3 10-BASE-T (Ethernet)	Supported
IEEE 802.3u 100-BASE-TX (Fast Ethernet)	Supported

ComX Computers

Product Specification Sheet

IEEE 802.3ab 1000-BASE-T (Gigabit Ethernet)	Supported
IEEE 802.3x Flow Control (Full-Duplex Flow Control)	Supported
IEEE 802.3af Power over Ethernet	Supported
IEEE 802.3at Power over Ethernet Plus	Supported
Ethernet Performance	
MAC Address	8 K
Buffer Memory	96 KB
Transmission Method	Store and Forward
Backplane	10 Gbps
Jumbo Frame	9 K
Auto-MDI/MDI-X, Auto-Negotiation	Supported
Filtering/Forwarding Rates	
10Mbps	14,880 pps
100Mbps	148,000 pps
1000Mbps	1,488,000 pps
Transmission Media	
10Base T	Cat. 3, 4, 5 UTP/STP
100Base TX	Cat. 5, 5e UTP/STP
1000Base T	Cat. 5e, 6, 7 UTP/STP
	* It is highly recommended to use standard Cat. 5e/6/7 cables which are compliant with the 3P/ETL standard.
PoE Function	
Number of PoE Out Ports	4
PoE Power Output	Per Port 56VDC, Max. 30W
Total PoE Power Budget	60 W
802.3at/af Standard Compatible	Yes
Over Current Protection	Supported
Circuit Shorting Protection	Supported
Power Pin Assignment	1/2(+), 3/6(-)
PoE PD Auto Detection	Yes
General	
LED Indicators	Power, Uplink, LAN ports x4, PoE ports x4
Power Input	100~240V AC / 50~60Hz
Power Consumption	65 W
Operating Temperature	0 degreesC ~ 50 degreesC (32 degreesF ~ 122 degreesF)

ComX Computers

Product Specification Sheet

Storage Temperature	-20 degreesC ~ 70 degreesC (-4 degreesF ~ 158 degreesF)
Operating Humidity	10~90% (Non-condensing)
Dimensions	160 (L) x 123 (W) x 44 (H) mm
Weight	0.8 kg
Safety Certifications	CE, C-Tick, FCC, LVD, VCCI
Accessories	
Included Accessories	Power cord, QIG

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/VIVOTEK-AW-GET-050A-065-Vivotek-unmanaged-4x-Gigabit-Buy-p-254843.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-08 10:50:45.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.