

VIVOTEK IP9171-HP

Vivotek IP9171-HP Fixed Network Camera

Product Overview

Vivotek IP9171-HP Fixed Network Camera, H265 Compression, Smart Stream II, Bandwidth SaVING, WDR Pro, SVN, GbE Port, DIS



Specifications

Overview:

VIVOTEK's IP9171-HP is a brand-new professional H.265 box network camera offering up to 30 fps at 3-Megapixel with superb image quality. By utilizing VIVOTEK's sophisticated Smart Stream II, the camera is able to optimize resolution for a desired object or area and thus ensure maximum efficiency of bandwidth usage. Combining both H.265 and Smart Stream II, the IP9171-HP can reduce both bandwidth and storage consumption by up to 80%* while maintaining the high standard of image quality. This unique combination of high resolution and low storage consumption make the IP9171-HP suitable for a wide range of video surveillance applications, including government and industrial buildings, retail environments, airports, railway stations and schools.

Additionally, employing WDR Pro, a True WDR allows the camera to capture both the dark and bright areas of an image, combining the differences to create a highly realistic representation of the original scene. Further improving the IP9171-HP's range of operating conditions, SNV technology makes high-quality full-color surveillance video possible under low-light conditions. Together, these features enable the camera to provide video quality strikingly close to the capabilities of the human eye. Further enhancing the camera's ability to adapt to its environment, precise software controls maintain the iris opening of the IP9171-HP's lens at an optimal level at all times, resulting in superior sharpness as well as depth of field. Finally, the IP9171-HP is also endowed with VIVOTEK's RBF (Remote Back Focus) System, empowering the installer to adjust focus both precisely and with greater flexibility.

Features:

- H.265 Compression Technology
- 30 fps @ 2048x1536
- P-iris Lens
- Smart Stream II to Optimize Bandwidth Efficiency
- WDR Pro, a True WDR for Unparalleled Visibility in High Contrast Environments
- Remote Back Focus for Easy Focus Adjustments

ComX Computers

Product Specification Sheet

- SNV (Supreme Night Visibility) for Low Light Conditions
- Video Rotation for Corridor View
- Lens Profile to Ensure the Full Compatibility for Different Lens Options
- Gigabit Ethernet for High Speed of Transmission
- Snapshot Focus
- DIS (Digital Image Stabilization)
- VIVOCLOUD App & Portal for 24/7 Surveillance (manually upload VIVOCLOUD VADP package)

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	VIVOTEK IP9171-HP
System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	128 MB
RAM	512 MB
Camera Features	
Image Sensor	1/2.8" Progressive CMOS
Maximum Resolution	2048x1536 (3MP)
Lens Type	Vari-Focal
Focal Length	f= 2.8 ~ 8 mm
Aperture	F1.2 ~ F1.95
Auto-iris	P-iris
Field of View	51 degrees~114 degrees (Horizontal)
	39 degrees~84 degrees (Vertical)
	63 degrees~143 degrees (Diagonal)
Shutter Time	1/5 sec. to 1/16, 000 sec.
WDR Technology	WDR Pro, a True WDR
Day/Night	Removable IR-cut filter for day & night function
Minimum Illumination	0.01 Lux @ F1.2 (Color)
	0.001 Lux @ F1.2 (B/W)
Pan/Tilt/Zoom Functionalities	ePTZ:
	48x digital zoom (4x on IE plug-in, 12x built in)
On-board Storage	Slot Type: MicroSD/SDHC/SDXC card slot
	Seamless Recording
Video	
Compression	H.265 & H.264 & MJPEG

ComX Computers

Product Specification Sheet

Maximum Frame Rate	H.265 & H.264:
	30fps @ 2048x1536
	MJPEG:
	15fps @ 2048x1536
Maximum Streams	3 simultaneous streams
S/N Ratio	60 dB
Dynamic Range	True WDR, 100dB
Video Streaming	Adjustable resolution, quality and bitrate
	Smart Stream II
Image Settings	Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings, video rotation, 3DNR, defog, Snapshot Focus, Lens Profile, DIS
Audio	
Audio Capability	Two-Way Audio (full duplex)
Compression	G711, G726
Interface	External microphone input
	Audio output
Network	
Users	Live viewing for up to 10 clients
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/ RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS
Interface	10 Base-T/100 Base-TX /1000 Base-T Ethernet (RJ-45)
	*It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Supported, specification available at www.onvif.org
Intelligent Video	
Video Motion Detection	Five-window video motion detection
VCA	Line crossing detection, field detection, loitering detection
Alarm and Event	
Alarm Triggers	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server, SD Card
	File upload via HTTP, SMTP, FTP, NAS server and SD card
General	
Smart Focus System	Remote Back Focus via UI

ComX Computers

Product Specification Sheet

Connectors	RJ-45 cable connector for 10/100/1000Mbps
	Network/PoE connection
	Audio input
	Audio output
	DC 12V power input
	AC 24V Power input
	Digital input*3
	Digital output*1
	RS485
LED Indicator	System power and status indicator
Power Input	DC12 V/AC 24V
	IEEE 802.3af/at PoE Class 0
Power Consumption	Max. 8.6 W
Dimensions	210 (D) x 70 (W) x 63 (H) mm
Weight	623 g
Safety Certifications	CE, LVD, FCC Class B, VCCI, C-Tick, UL
Operating Temperature	Starting Temperature: 0 degreesC ~ 50 degreesC (32 degreesF ~ 122 degreesF)
	Working Temperature: -10 degreesC ~ 50 degreesC (14 degreesF ~ 122 degreesF)
Humidity	0.9
System Requirements	
Operating System	Microsoft Windows 7/8/Vista/XP/2000
Web Browser	Mozilla Firefox 7~10 (streaming only)
	Internet Explorer 7/8/9/10/11
Other Players	VLC: 1.1.11 or above
	Quicktime: 7 or above
Included Accessories	
CD	User's manual, quick installation guide, Installation Wizard 2, VAST
Others	Quick installation guide, mounting bracket, screw pack, Lens

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/VIVOTEK-IP9171-HP-Vivotek-IP9171-HP-Fixed-Network-Camera-Buy-p-208567.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

ComX Computers

Product Specification Sheet

PDF generated: 2026-10-08 04:01:14.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.