ComX Computers
Product Specification Sheet

WAR-1000A

PCM Warrior 1000VA Line-Interactive UPS





Specifications

Overview:

Compact Line-interactive UPS series Black Knight designed to protect personal computers and small workstations from the major problems with power supply: high emissions of electromagnetic and radio frequency interference, slides, promotions and extinction voltage sources.

Features:

-
- Compact design for storage convenience
- Built-in automatic voltage regulator (AVR)
- Simulated sine wave output waveforms
- Green mode setting for energy saving
- Automatic self-diagnostic and alarm warnings
- Surge, short circuit, and overload protections
- Advanced battery management (ABM)
- Scheduling shutdown & reboot function on AP models
- Events recorder of power incidents on AP models

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Product Code	WAR-1000A
Specifications	
INPUT	
Voltage	110V /115V / 120V +/-25%
	220V /230V / 240V +/-25%
Frequency	50Hz / 60Hz +/-10% auto sensing

OUTPUT	
Voltage	110V /115V / 120V +/-5%
	220V /230V / 240V +/-5%
AVR	When input voltage between -9% to -25% of nominal, increase output by 15%.
	When input voltage between +9% to +25% of nominal, decrease output by 13%.
Frequency	50Hz / 60Hz +/-1Hz
Waveform	Simulated sinewave
Connections	*Please refer below "Receptacle Options". Customized receptacle can be discussed.
Transfer time	4 milliseconds including detection time (typical)
PROTECTION	
Overload	UPS automatic power off if overload exceeds 105% of nominal at 60 seconds; 130% at 3 seconds
Surge	110V /115V / 120V with 265 Joules, 8/20uS
	220V /230V / 240V with 460 Joules, 8/20uS
Short circuit	UPS output cut off immediately or protected by input circuit breaker
Tele-communication	RJ45 x2 (input and output)
Fuse	Yes (circuit breaker)
Alarm	Buzzer beeps under backup mode, battery low, battery charging fault, and overload
BATTARY	
Type	Sealed, maintenance-free lead acid battery
Typical recharge time	6 hours to 90%
Battery quantity	12V 9h x1
Backup time for one PC	Approximately 25 minutes
Protection	Automatic diagnostics, over-discharge and short circuit protection by fuse
STANDARDS	
Dimension (W x D x H)	99mm x 315mm x 145mm
Product weight	
Display	LED indicator
Communication interface	*Optional - none or USB B-type
Audible noise	< 40dBA (1m from surface)
Ambient operation	Maximum elevation at 2000m, 0 to 40°C, 0 to 95% humidity (non-condensing)
Storage condition	Maximum 15000m

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/WAR-1000A-PCM-Warrior-1000VA-Line-Interactive-UPS-p-68818.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 11:47:52.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.