ComX Computers
Product Specification Sheet

XONAR_D2/PM/A

ASUS XONAR D2 Sound Card

Product Overview

ASUS XONAR D2 - 7.1 Channel PCI Sound Card



Specifications

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	XONAR_D2/PM/A

Audio Performance	Output Signal-to-Noise Ratio (A-Weighted):
	118dB for all channels dB
	Input Signal-to-Noise Ratio (A-Weighted):
	118 dB
	Output THD+N at 1kHz:
	0.0004% (-108dB)
	Input THD+N at 1kHz:
	0.0004% (-108dB)
	Frequency Response (-3dB, 24-bit / 96kHz input):
	Frequency Response (-3dB, 24-bit / 192kHz input):
	Output / Input Full-Scale Voltage
	2 Vrms (5.65 Vp-p)
	Sample Rate Conversion Quality:
	Almost lossless, high-fidelity floating-point filters, which has:
	-140dB THD+N (typical value for 44.1K->48KHz, 24bit)
	-145dB Dynamic Range (typical value for 44.1K->48KHz, 24bit)
Main Chipset	Audio Processor:
	ASUS AV200 High-Definition Sound Processor (Max. 192KHz / 24bit)
	24-bit D-A Converter of Digital Sources:
	Burr-Brown PCM1796 *4 (123dB SNR, Max. 192kHz / 24bit)
	24-bit A-D Converter for Analog Inputs:
	Cirrus-Logic CS5381* 1 (120dB SNR, Max. 192kHz / 24bit)
Sample Rate and Resolution	Analog Playback Sample Rate and Resolution:
	44.1K / 48K / 96K / 192KHz @ 16 / 24bit
	Analog Recording Sample Rate and Resolution:
	44.1K / 48K / 96K / 192KHz @ 16 / 24bit
	S / PDIF Digital Output:
	Dolby Digital, DTS, WMA-Pro
	S / PDIF Digital Input:
	44.1K / 48K / 96K / 192KHz @ 16 / 24bit
	ASIO 2.0 Driver Support:
	44.1K / 48K / 96K / 192KHz @ 16 / 24bit

I / O Ports	Analog Output Jack:
	3.50mm mini jack *4 (Front / Side / Center-Subwoofer / Back)
	Analog Input Jack:
	3.50mm mini jack *2 (Line-In / Mic-In)
	Other line-level analog input (for CD-IN / TV Tuner):
	CD-In, Aux-In (4-pin header on the card)
	Digital S / PDIF Output:
	Coaxial and High-bandwidth Optical Combo Connector
	Supports 192KHz / 24bit
	Digital S / PDIF Input:
	Coaxial and High-bandwidth Optical Combo Connector
	Supports 192KHz / 24bit
	MIDI Ports:
	Additional MPU-401 MIDI I / O bracket and converter cable

Driver Features	Operation System:
	Windows 7 / Vista / XP / MCE2005
	Dolby Technologies:
	Dolby Digital Live
	Dolby Digital Live encodes any audio signal on PC in real-time to Dolby Digital (AC3) 5.1 surround sounds to your home theater environment through one single S / PDIF connection
	Dolby Headphone
	Dolby Headphone technology allows users to listen to music, watch movies, or play games with the dramatic 5.1-channel surround or realistic 3D spacious effects through any set of stereo headphones.
	Dolby Virtual Speaker
	Dolby Virtual Speaker technology simulates a highly realistic 5.1-speaker surround sound listening environment from as few as two speakers.
	Dolby Pro-Logic IIx
	Dolby Pro-Logic II is the well-known technology to process any native stereo or 5.1-channel audio into a 6.1- or 7.1- channel output, creating a seamless, natural surround soundfield.
	DTS Technologies:
	DTS Connect (DTS Interactive Encoder and DTS Neo:PC)
	Smart Volume Normalizer:
	Normalizes the volume of all audio sources into a constant level
	Xear 3D Virtual Speaker Shifter:
	Virtual 7.1 speaker positioning
	Magic Voice:
	Modifies the sound of your voice, for VOIP and online chat applications (Windows XP)
	Karaoke Functions:
	Music Key-Shifting and Microphone Echo effects (Windows XP)
	FlexBass:
	Professional Bass Management / Enhancement system
	Other Effects:
	10-band Equalier / 27 Environment Effects
	3D Sound Engines / APIs:
	Vista: DirectSound3D GX 2.5, DirectSound HW, DirectSound SW, A3D1.0, OpenAL generic modes, 128 3D sounds processing capability
	XP: DirectSound2.5 SW, A3D1.0, OpenAL generic modes, 128 3D sounds processing capability
	DirectX:
	DirectX 9.0 or above required for 7.1ch output

Bundled Software Utility	Portable Music Processor utility:
	Backup digital music content or CD audio into regular MP3 / WMA files with Dolby Headphone, Dolby Virtual Speaker (w / Pro-Logic II), and Smart Volume Normalization processing (Windows Media Player 10 or above is required)
	Professional Audio Editing Utility:
	1. Ableton Live Lite
	2. Cakewalk Production Plus Pack (SONAR LE, Dimension LE, and Project5 LE)
	PowerDVD 7.0:
	Software DVD player with Dolby Digital 5.1 decoder
Accessories	4 x 3.5mm-to-RCA adaptor cable (8ch)
	2 x S / PDIF optical adaptors
	1 x S / PDIF optical cable
	1 x Additional MIDI card, cable, and external standard MIDI adaptor Y cable
	Dolby Demo CD
Size (Width x Height)	106.5 x 180.26mm

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/XONAR_D2-PM-A-ASUS-XONAR-D2-Sound-Card-p-81182.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-17 03:19:22.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.