

YST-TA410

Yeastar TA410 4 port FXO VoIP Gateway

Product Overview

Yeastar TA410 4 port FXO VoIP Gateway, 4x RJ11 FXO Ports, 1x 10/100 Mbps LAN, Fully compliant with SIP and IAX2



Specifications

Overview:

TA Series FXO VoIP Gateway

- A cost-effective and reliable solution for office-to-office voice connectivity
-
- Connect analog telephone lines or PABX extension interface to VoIP networks.
- Businesses of all sizes can rely on this innovative solution.
- Toll-quality voice call and top performance and reliability.

Feature-rich

A robust feature set that fulfills your various needs and cuts communication cost

Simple and Easy

User-friendly Web GUI and intuitive operations. Comprehensive call log, system logs, hardware logs, and debug logs

High Performance

Superb voice compression with industry standard codecs. Tested and certified with Elastix and compatible with other IP

ComX Computers

Product Specification Sheet

systems

Auto Provisioning

Support PnP or DHCP provisioning by Yeastar PBX and standard open protocol TR-069

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	YST-TA410
Models	TA410
RJ11 FXO Ports	4
RJ 21 Ports	?
LAN	1 10/100Mbps
WAN	?
Protocol	SIP (RFC3261), IAX2
Transport	UDP, TCP, TLS, SRTP
Codec	G.711 (alaw/ulaw), G.722, G.723, G.726, G.729A, GSM, ADPCM
Voice Capability	ITU-T G.168 LEC Echo Cancellation, Dynamic Jitter Buffer, VAD, CNG, PLC
DTMF Mode	RFC2833, SIP Info, In-band
Fax	T.30
QoS	DiffServ, ToS, 802.1 P/Q VLAN tagging
Network	DHCP, DDNS, OpenVPN, PPPoE, Static Route, VLAN
Network Protocol	FTP, TFTP, HTTP, HTTPS, SSH
Management Protocol	RADIUS
Remote Management	N/A
Signaling	FXS Loop Start, FXS Kewl Start
Caller ID	BELL202, ETSI (V23), NTT (V23-Japan), and DTMF-based CID
Disconnect Methods	Busy Tone, Polarity Reversal
FXO Connectivity	Programmable AC Impedance, Hangup Detection, Answer Detection, Caller ID Detection
Power	12V, 1A
Dimensions (L x W x H) (mm)	200 x 137 x 25
Operation Range	0 degreesC to 40 degreesC, 32 degreesF to 104 degreesF
Storage Range	-20 degreesC to 65 degreesC, -4 degreesF to 149 degreesF
Humidity	10-90% non-condensing
Mounting	Desktop, Wall-mount
Compatibility	Interoperable with Asterisk, Lync Server, FreePBX and certified with Elastix.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/YST-TA410-Yeastar-TA410-4-port-FXO-VoIP-Gateway-Buy-p-304940.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-16 13:55:11.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.