ComX Computers
Product Specification Sheet

ZK-IN05-A/ID

ZKTeco IN05-A F/P TA Terminal + RFID

Product Overview

ZKTeco IN05-A F/P TA Terminal + RFID



Specifications

Overview:

IN05 is a fingerprint identification time & attendance and access control terminal, which can connect with third party electric lock, door sensor and exit button etc. Communicating via Wi-Fi, TCP/IP, 3G and USB host, it ensures a smooth connection and data transfer. It's associated with ZK new fingerprint reader, the operation remains stable under strong light source and high preciseness of verification of wet and rough fingers. Amazing verification speed and intuitive Operation process make it popular. It will match your slap-up office perfectly.

Features:

- Built in PoE
- 1 channel auxiliary input for smoke detector connection
- Built in battery, up to 4 hours
- Multiple communicate mode, Wi-Fi, TCP/IP, 3G, USB host
- Stable operation under strong light source
- Advance access function including Lock connection, alarm, Wiegand input/output

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	ZK-IN05-A/ID
Main	
Biometric	Fingerprint

RF Optional	125kHz EM / 13.56MHz MF
Capacity	
Max User(1:N)	10, 000
Max Fingerprint (1:N)	3, 000 standard / 10, 000 Optional
Max Record	100, 000
Interface	
TCP/IP	10/100 M
PoE Optional	802.3 at 28W
Wi-Fi	802.11 B/G/N
3G Optional	WCDMA
USB	USB 2.0 (Host)
RS232	1 port for external printer
RS485	1 port for FP reader
Relay	2 relays
Wiegand	1ch In & Out
Input	1 Input
Hardware	
LCD	3.0" Color LCD
Sound	24-bit
Operating Temp.	0 degreesC - 45 degreesC
Operating Humidity	20% ~ 80%
Power	DC 12V 3A
Dimensions(W x H x D mm)	213*155*107.81mm
Certificates	CE, FCC, RoHS
Function	
Standard	Automatic Status Switch, Self-Service Query, DST, T9 Input, 9 Digit
	User ID, Scheduled Bell, Photo ID, Lock, sensor, Exit button
Optiona	ID / MF, ADMS
Compatibility	

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/ZK-IN05-A-ID-ZKTeco-IN05-A-F-P-TA-Terminal-RFID-p-185511.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-15 12:30:16.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.