ComX Computers
Product Specification Sheet

ZK-PB4060-L

ZKTeco PB4060L 6 Meter Boom Barrier

Product Overview

ZKTeco PB4060L 6 meter Boom barrier, 6 second opening time, Chassis on left, Boom on right, Without InBio controller



Specifications

Features:

- Supports external infrared radiation and vehicle loop detector for anti-crash function
- Die-casting aluminum alloy motor with double strong springs makes the operation more stable
- Wheel manual release in case of power cut, rotate the wheel manual release on the bottom of the motor to raise the boom manually
- The housing with modularised design is made of power coated steel which offers the best protection against corrosion
- Built-in cooling fan, solving the problem of heat-protection, operating temperature of motor ranged from -40 degreesC - +140 degreesC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx.co.za/ZK-PB4060-L-ZKTeco-PB4060L-6-Meter-Boom-Barrier-p-245088.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx.co.za/terms-of-use.php
Terms of Sale: https://www.comx.co.za/terms-of-sale.php

PDF generated: 2026-11-10 00:01:09.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.