DS-PK1-E-WE



- 868 MHz two-way wireless communication
- AES-128 encryption
- Stay/away arming, disarming, alarm clearing for specified area or all areas
- LED indicates the programmed area
- One-Push fire alarm, panic alarm, and medical alarm. Silent/Audible alarm selectable. etc.
- Output control
- Full touch key design with LED backlight
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Easy replaceable battery
- Frequency hopping against jamming for reliable transmission

▪ Specification

Electrical characteristics	
Battery type	Four AA batteries
Power supply	Battery Supply
Operation humidity	10% to 90% (No condensing)
Operation temperature	-10 °C to +55 °C (-4 °F to +122 °F)
Battery life span	Up to 2 years (standby time)
Wireless transmission	
RF frequency	868 MHz
RF modulation	2GFSK
RF distance	1200m (open area
General	
Installation method	Screw mounting
Dimension(WxHxD)	140 (5.50") x 86 (3.38") x 22 (0.87") mm
Weight	151 g (5.33 oz) without battery

▪ Available Model

DS-PK1-E-WE

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.

Hikvision HikvisionHQ HikvisionHQ Hikvision_Global Hikvision Corporate Channel hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 I Data subject to change without notice I